

Perfect Valves For The World !



Qingdao Elite Machinery Manufacture Co., Ltd.

Add: No.155, Haier Road, Jimo District, Qingdao, China

Phone: 400-697-6268

Web: www.esgvalve.cn www.esgvalve.com

Email: info@esgvalve.com




ESG Corporate Website




ESG Official Wechat

2025 English edition



QINGDAO ELITE MACHINERY MANUFACTURE CO., LTD.

INDUSTRIAL FLOW CONTROL EXPERT




Elite | **S**ervice | **G**lobal

Perfect Valves For The World !
Be the industry benchmark
and create a century-old enterprise

Qingdao Elite Machinery Manufacturing Co., Ltd. (hereinafter referred to as "ESG") is a high-tech enterprise that integrates the research and development, production, and sales of valves. The company pays closely attention on customer needs and is committed to becoming a leader in fluid process control system solutions.

Since its establishment in 2001, ESG has obtained over 100 patents, including 10 invention patents. Various mainstream valve series products such as angle seat valves, shuttle valves, diaphragm valves, butterfly valves, ball valves, drain valves, and membrane plug valves have been widely praised by customers. Valve products are exported to 82 countries, covering 19 key industries such as nuclear industry, new energy, medicine, food and



Provide System Solutions
Create More Value For Users In Various Industries

EPS Molding、Industrial Gas、Textile Dyeing、Ceramic、Casting、Fodder、Water Treatment、Environmental、Chemical、Electricity、Papermaking、Metallurgy、Automobile、Pharmaceutical、Food & Beverage、New Energy、Solar Energy、Semiconductor、Rubber



Our Customers



Product Catalog

 Y-type Angle Seat Valve 06-41	 Proportional Control Angle Seat Valve 42-57	 Multi-channel Valve 58-67	 Filling Valve 68 - 75	 Shuttle Valve 76-84	 Pneumatic Butterfly Valve 85-88	 Ball Valve 89-101
 Check Valve 102-106	 Strainer 107-109	 Pressure Reducing Valve/Overflow Valve 110-111	 Steam Trap 112 - 120	 Other Valves 121-124	 Shut Off Valve/Regulating Valve 125-134	 Control Accessory 135-137

Angle Seat Valve



ESG angle seat valve is made entirely of high-quality stainless steel, ensuring stable operation of the valve even in harsh conditions, with corrosion resistance and wear resistance. The valve is precisely designed and can be used in conjunction with the ESG positioner to achieve precise flow and pressure control, meeting needs of various industrial applications. The internal structure of the valve is optimized with sealing and wear-resistant materials, ensuring a long service life for the valve. Even under high-frequency switching conditions, it can maintain stable sealing performance and good operating performance. In terms of configuration options, it includes different materials, connection methods, actuators and accessories to meet the needs of different users and application scenarios. Whether it is in the fine chemical processes that

Applications

Eps Molding, Industrial Gas, Textile Dyeing, Ceramic, Casting, Fodder, Water Treatment, Environmental, Chemical, Pharmaceutical, Food &



Angle Seat Valve with Multiple Configurations Available

Control Accessory



Position Indicator




Intelligent Positioner



Two-piece Intelligent Positioner



Solenoid Valve



Adjustable Seat



Proximity Switch

Actuator



Pneumatic Actuator



Manual Actuator

Valve Body



Two-Way Valve



Manifold Valve



Modular Valve



Three-Way Valve



Three-Way Low Flow Resistance Valve




Globe Valve



Shut Off Valve

Y-type Angle Seat Valve

100 Series
Threaded Angle
Seat Valve100 Series
Welded Angle
Seat Valve100 Series
Tri-clamp Angle
Seat Valve100 Series Flanged
Angle Seat Valve
with Round Bonnet100 Series Flanged
Angle Seat Valve
with Square Bonnet

Technical Specification

- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: PTFE
- Actuator material: CF8 (40mm–90mm Actuator)、AL (125mm Actuator)
- Actuator size: 40mm, 50mm, 63mm, 90mm, 125mm
- Applicable fluid: Water, Alcohol, Oil, Fuel, Steam, Neutral gas or Liquid, Organic solvent, Acid and lye
- Fluid viscosity: Max 600mm²/s
- Fluid temperature: –10°C — +180°C
–40°C — +180°C
+25°C — +220°C
- Ambient temperature: –10°C — +80°C
- Control type: Single acting normally closed,
Single acting normally open,
Double acting normally closed,
Double acting without spring
- Connection type: Threaded, Welded, Flanged, Tri-clamp


Advantages

1. Large flux, low resistance, prevent water-hammer.
2. Y-type raises flux by 30% and make flow more smooth.
3. Long working life.
4. The stem adjusts and lubricates itself automatically, minimizing needs for maintaince.
5. The stainless steel actuator can be rotated 360° for flexiable

Function Principle


Valve stays closed(open) by spring force in its normal state. When piston is actuated by compressed air, valve becomes opened (closed). For double acting type, valve is opened and closed by

Y-type Angle Seat Valve



Main Dimension (Threaded Connection)

Size	Actuator (mm)	Q	C	R	K	G	T	A	L	SW
DN8	40	1/8"	50.5	27	112	1/4"	12	124	68	27
	50	1/8"	60	33	125			135		
DN10	40	1/8"	50.5	27	112	3/8"	12	124	68	27
	50	1/8"	60	33	125			135		
DN15	40	1/8"	50.5	27	112	1/2"	15	124	68	27
	50	1/8"	60	33	125			135		
DN20	50	1/8"	60	33	132	3/4"	16	140	75	32
DN25	50	1/8"	60	33	136	1"	17	150	90	40
	63	1/8"	75	41	162			172		
DN32	63	1/8"	75	41	174	1 1/4"	21	190	116	50
	90	1/8"	106	55	223			235		
DN40	63	1/8"	75	41	175	1 1/2"	21	190	116	56
	90	1/8"	106	55	223			235		
DN50	63	1/8"	75	41	183	2"	22	205	138	69
	90	1/8"	106	55	232			250		
	125AL	1/4"	170	85	300			305		
DN65 Square bonnet	90	1/8"	106	55	280	2 1/2"	26	275	178	85
	125AL	1/4"	170	85	330			320		
DN80 Square bonnet	125AL	1/4"	170	85	355	3"	27	340	210	100




Main Dimension (Welded Connection)

Size	Actuator (mm)	Q	C	R	K	HA	HL	Chamfer		DIN11850-2		DIN11850-3	
								ΦD*	S*	ΦD	S	ΦD	S
DN15	40	1/8"	50.5	27	112	118	70	22	3.5	19	1.5	20	2
	50	1/8"	60	33	125	128							
DN20	50	1/8"	60	33	132	135	82	29	5	23	1.5	24	2
DN25	50	1/8"	60	33	136	150	100	35	5	29	1.5	30	2
	63	1/8"	75	41	162	175							
DN32	63	1/8"	75	41	174	186	125	39	4	35	1.5	36	2
	90	1/8"	106	55	223	232							
DN40	63	1/8"	75	41	175	190	130	45	4.5	41	1.5	42	2
	90	1/8"	106	55	223	235							
DN50	63	1/8"	75	41	183	206	155	57	4	53	1.5	54	2
	90	1/8"	106	55	232	250							
	125AL	1/4"	170	85	300	307							
DN65 Square bonnet	90	1/8"	106	55	280	320	270	75	5	70	2	-	-
	125AL	1/4"	170	85	330	360						-	-
DN80 Square bonnet	125AL	1/4"	170	85	355	360	284	90	5.5	85	2	-	-

Note: * designates design dimension (the actual dimension may vary)


Y-type Angle Seat Valve



Flange specification: DIN2543/DIN2576/EN1092-1/HG20592; ISO/ANSI/DIN/JIS customization available.

Main Dimension (Flange Connection)

Size	Actuator (mm)	Q	A	B	L	C	H	ΦE	n-ΦF	ΦM	ΦN	ΦP	α
DN15	40	1/8"	135	125	130	2	14	65	4-14	16	45	95	45°
	50		145	140									
DN20	50	1/8"	165	140	150	2	14	75	4-14	19	56	105	45°
DN25	50	1/8"	170	145	160	2	14	85	4-14	26	65	115	45°
	63		190	175									
DN32	63	1/8"	190	188	180	2	16	100	4-18	31	78	140	45°
	90		230	235									
DN40	63	1/8"	206	190	200	3	16	110	4-18	38	84	150	45°
	90		250	240									
DN50	63	1/8"	235	195	230	3	16	125	4-18	54	100	165	45°
	90		277	245									
	125AL	1/4"	330	310									
DN65 Square bonnet	90	1/8"	330	280	290	3	18	145	4-18	71	120	185	45°
DN80 Square bonnet	125AL	1/4"	375	330									
DN80 Square bonnet	125AL	1/4"	380	355	310	3	20	160	8-18	84	135	200	22.5°
DN100 Square bonnet	125AL	1/4"	420	395	350	3	20	180	8-18	96	155	215	22.5°



Clamp Specification: ISO 2852; customization available.

Main Dimension (Tri-clamp Connection)


Size	Actuator (mm)	Q	A	K	L	ΦC	ΦB	Φd*	ΦD
DN15	40	1/8"	130	115	80	20.5	27.5	15	34
	50	1/8"	140	126					
DN20	50	1/8"	158	148	130	25	43.5	19	50.5
DN25	50	1/8"	165	140	130	32	43.5	27	50.5
	63	1/8"	188	166					
DN32	63	1/8"	200	174	146	37	43.5	31	50.5
	90	1/8"	245	223					
DN40	63	1/8"	210	175	160	40	56.5	34	64
	90	1/8"	255	223					
DN50	63	1/8"	221	185	175	53	56.5	45	64
	90	1/8"	265	235					
	125AL	1/4"	325	296					
DN65 Square bonnet	90	1/8"	325	280	278	75	83.5	65	91
DN80 Square bonnet	125AL	1/4"	360	330					
DN80 Square bonnet	125AL	1/4"	360	352	290	89.5	97	78.5	106

Note: * designates design dimension (the actual dimension may vary)

Y-type Angle Seat Valve


Single Acting, Normally Closed (NC)–Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	9.5	1.8	28	0–1.0	0.5–0.7
		13	2.2	40	0–1.6	0.4–0.45
				50	0–1.6	0.35–0.4
DN10	G3/8"	9.5	2.2	28	0–1.0	0.5–0.7
		13	3.9	40	0–1.6	0.4–0.45
				50	0–1.6	0.35–0.4
DN15	G1/2"	9.5	2.2	28	0–1.0	0.5–0.7
		13	4.3	40	0–1.6	0.4–0.45
				50	0–1.6	0.35–0.4
DN20	G3/4"	18	7.6	50	0–1.6	0.35–0.5
DN25	G1"	24	15.8	50	0–1.6	0.35–0.55
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.4
				90	0–1.6	0.3–0.35
				63	0–1.6	0.3–0.7
DN40	G1 1/2"	35	32.0	90	0–1.6	0.3–0.4
DN50	G2"	45	52.0	63	0–0.9	0.3–0.7
				90	0–1.6	0.3–0.45
				125	0–1.6	0.3–0.4
				90	0–1.0	0.3–0.6
DN65	G2 1/2"	61	83.2	125	0–1.6	0.3–0.4
DN80	G3"	80	119	125	0–1.2	0.3–0.7



Single Acting, Normally Closed (NC)–Enter Below Seat (Minimize water-hammer)


Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	9.5	1.8	28-A	0–1.0	≥0.5
		13	2.2	40-A	0–1.3	≥0.4
				50-A	0–1.4	≥0.45
DN10	G3/8"	9.5	2.2	28-A	0–1.0	≥0.5
		13	3.9	40-A	0–1.3	≥0.4
				50-A	0–1.4	≥0.45
DN15	G1/2"	9.5	2.2	28-A	0–1.0	≥0.5
		13	4.3	40-A	0–1.3	≥0.4
				50-A	0–1.4	≥0.45
DN20	G3/4"	18	7.6	50-A	0–1.4	≥0.45
DN25	G1"	24	15.8	50-A	0–0.8	≥0.45
				63-A	0–1.3	≥0.5
				63-B	0–0.8	≥0.3
DN32	G1 1/4"	31	26.0	63-A	0–0.6	≥0.5
				90-A	0–1.6	≥0.6
				90-B	0–1.3	≥0.45
DN40	G1 1/2"	35	32.0	63-A	0–0.5	≥0.5
				90-A	0–1.6	≥0.6
				90-B	0–1.1	≥0.45
DN50	G2"	45	52.0	63-A	0–0.2	≥0.5
				90-A	0–1.0	≥0.6
				90-B	0–0.7	≥0.45
				125-A	0–1.6	≥0.55
				125-B	0–1.1	≥0.45
				90-A	0–0.5	≥0.6
DN65	G2 1/2"	61	83.2	90-B	0–0.2	≥0.45
				125-A	0–0.9	≥0.55
				125-B	0–0.6	≥0.45
				125-D	0–0.5	≥0.35
				125-A	0–0.5	≥0.55
				125-B	0–0.3	≥0.45
DN80	G3"	80	119	125-C	0–0.2	≥0.4
DN100	G4"	90	132	125-A	0–0.25	≥0.55



Note: In order to ensure product performance, it is recommended to select product according to the highest value in the ≤ 90% pressure range


Double Acting, Normally Closed (NC)–Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	0.4–0.45
				50	0–1.6	0.35–0.4
DN10	G3/8"	13	3.9	40	0–1.6	0.4–0.45
				50	0–1.6	0.35–0.4
DN15	G1/2"	13	4.3	40	0–1.6	0.4–0.45
DN20	G3/4"	18	7.6	50	0–1.6	0.35–0.5
DN25	G1"	24	15.8	50	0–1.6	0.35–0.55
				63	0–1.6	0.3–0.4
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.55
				90	0–1.6	0.3–0.35
				63	0–1.6	0.3–0.7
DN40	G1 1/2"	35	32.0	90	0–1.6	0.3–0.4
				63	0–0.9	0.3–0.7
DN50	G2"	45	52.0	90	0–1.6	0.3–0.45
				125	0–1.6	0.3–0.4
				90	0–1.0	0.3–0.6
DN65	G2 1/2"	61	83.2	125	0–1.6	0.3–0.4
				90	0–1.0	0.3–0.6
DN80	G3"	80	119	125	0–1.2	0.3–0.7



Double Acting, Normally Closed (NC)–Enter Below Seat (Minimize water-hammer)

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	≥0.4
				50	0–1.6	≥0.35
DN10	G3/8"	13	3.9	40	0–1.6	≥0.4
				50	0–1.6	≥0.35
DN15	G1/2"	13	4.3	40	0–1.6	≥0.4
DN20	G3/4"	18	7.6	50	0–1.6	≥0.35
DN25	G1"	24	15.8	50	0–1.3	0.3–0.6
				63	0–1.6	0.3–0.4
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.6
				90	0–1.6	0.3–0.4
DN40	G1 1/2"	35	32.0	63	0–1.6	0.3–0.7
				90	0–1.6	0.3–0.5
DN50	G2"	45	52.0	63	0–0.8	0.3–0.75
				90	0–1.6	0.3–0.6
				125	0–1.6	0.3–0.4
DN65	G2 1/2"	61	83.2	90	0–1.1	0.3–0.7
				125	0–1.6	0.3–0.55
DN80	G3"	80	119	125	0–1.6	0.3–0.7
DN100	G4"	90	132	125	0–1.2	0.4–0.6




Note: In order to ensure product performance, it is recommended to select product according to the highest value in the ≤ 90% pressure range

Y-type Angle Seat Valve


Double Acting Without Spring–Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	0.3–0.45
				50	0–1.6	0.3–0.35
DN10	G3/8"	13	3.9	40	0–1.6	0.3–0.45
				50	0–1.6	0.3–0.35
DN15	G1/2"	13	4.3	40	0–1.6	0.3–0.45
				50	0–1.6	0.3–0.35
DN20	G3/4"	18	7.6	50	0–1.6	0.3–0.4
				50	0–1.6	0.3–0.4
DN25	G1"	24	15.8	50	0–1.6	0.3–0.45
				63	0–1.6	0.3–0.35
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.55
				90	0–1.6	0.3–0.4
DN40	G1 1/2"	35	32.0	63	0–1.6	0.3–0.65
				90	0–1.6	0.3–0.4
DN50	G2"	45	52.0	63	0–1.0	0.3–0.7
				90	0–1.6	0.3–0.45
				125	0–1.6	0.3–0.4
				90	0–1.0	0.3–0.6
DN65	G2 1/2"	61	83.2	125	0–1.6	0.3–0.4
				125	0–1.2	0.3–0.7



Double Acting Without Spring–Enter Below Seat (Minimize water-hammer)


Size	Thread end	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	0.3–0.4
				50	0–1.6	0.3–0.4
DN10	G3/8"	13	3.9	40	0–1.6	0.3–0.4
				50	0–1.6	0.3–0.4
DN15	G1/2"	13	4.3	40	0–1.6	0.3–0.4
				50	0–1.6	0.3–0.4
DN20	G3/4"	18	7.6	50	0–1.6	0.3–0.4
				50	0–1.6	0.3–0.65
DN25	G1"	24	15.8	50	0–1.6	0.3–0.55
				63	0–1.6	0.3–0.7
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.45
				90	0–1.6	0.3–0.5
DN40	G1 1/2"	35	32.0	63	0–1.2	0.3–0.75
				90	0–1.6	0.3–0.5
DN50	G2"	45	52.0	63	0–0.4	0.3–0.75
				90	0–1.6	0.3–0.6
				125	0–1.6	0.3–0.4
				90	0–1.0	0.3–0.75
DN65	G2 1/2"	61	83.2	125	0–1.6	0.3–0.6
				125	0–1.0	0.3–0.7
DN80	G3"	80	119	125	0–1.0	0.3–0.7
				125	0–0.8	0.3–0.75



Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range


Normally Open(NO)–Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	≥ 0.3
				50	0–1.6	≥ 0.3
DN10	G3/8"	13	3.9	40	0–1.6	≥ 0.3
				50	0–1.6	≥ 0.3
DN15	G1/2"	13	4.3	40	0–1.6	≥ 0.3
				50	0–1.6	≥ 0.3
DN20	G3/4"	18	7.6	50	0–1.2	≥ 0.3
				50	0–1.2	≥ 0.3
DN25	G1"	24	15.8	50	0–0.3	≥ 0.3
				63	0–1.6	≥ 0.45
DN32	G1 1/4"	31	26.0	63	0–1.4	≥ 0.45
				63	0–1.4	≥ 0.45
DN40	G1 1/2"	35	32.0	63	0–1.4	≥ 0.45
				63	0–0.6	≥ 0.45
DN50	G2"	45	52.0	63	0–0.6	≥ 0.45
				63	0–0.6	≥ 0.45



Normally Open(NO)–Enter Below Seat (Minimize water-hammer)

Size	Thread end	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	0.3–0.5
				50	0–1.6	0.3–0.4
DN10	G3/8"	13	3.9	40	0–1.6	0.3–0.5
				50	0–1.6	0.3–0.4
DN15	G1/2"	13	4.3	40	0–1.6	0.3–0.5
				50	0–1.6	0.3–0.4
DN20	G3/4"	18	7.6	50	0–1.6	0.3–0.6
				50	0–1.6	0.3–0.6
DN25	G1"	24	15.8	50	0–1.3	0.3–0.6
				63	0–1.6	0.3–0.5
DN32	G1 1/4"	31	26.0	63	0–1.3	0.3–0.6
				63	0–1.3	0.3–0.6
DN40	G1 1/2"	35	32.0	63	0–0.7	0.3–0.6
				90	0–1.6	0.3–0.45
DN50	G2"	45	52.0	63	0–0.5	0.3–0.6
				90	0–1.2	0.3–0.6
				125	0–1.4	0.3–0.7
				125	0–1.4	0.3–0.7
DN65	G2 1/2"	61	83.2	125	0–0.75	0.3–0.6
				125	0–0.75	0.3–0.6
DN80	G3"	80	119	125	0–1.4	0.3–0.7
				125	0–1.4	0.3–0.7



Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Y-type Angle Seat Valve

Angle Seat Valve
with Proximity Switch



Angle Seat Valve
with Solenoid Valve



Proximity Switch

Proximity switch can be mounted on angle seat valves of all sizes





Solenoid Valve

Apply to angle seat valve with any aperture size. Connect to 5/2 or

Technical Specification

- Operating pressure: 10–30V DC
- Protection class: IP67
- Detection distance: 3mm ± 10% (Customization available)
- Temperature range: –25°C — +70°C
- Enclosure material: brass nickel plating
- Probe material: ABS
- Leakage class: DIN EN 12266 Class A

Output signal



Angle Seat Valve
with Manual Override



Manual Override

It can adjust piston position, restrict travel, and regulate flow.
Applicable to all types of angle seat valves. It can be used for emergency control, in case of lack of control fluids or electrical/

Technical Specification

- Handwheel material: Die-casted Aluminum
- Control type: Single acting normally closed
- Leakage class: DIN EN 12266 Class A
- Suitable for 40/50/63/90mm actuator

Angle Seat Valve
with Position Indicator



Position Indicator


Position Indicator can be mounted on angle seat valves of all sizes

Technical Specification

- Operating Voltage: DC12V–DC36V (mechanical type)/
DC12V–DC30V(contactless type)
- Operating Current: MAX.300mA(mechanical type)/
MAX.100mA(contactless type)
- Indicator Light: Visually feedbacks the valve's open/close status
- Temperature Range: –10°C — +70°C
- Environment humidity: ≤90%RH
- Protection Level: IP65
- Explosion-Proof: Ex nA IIC T4
- Shell Material: PA6-GF30+PC
- On-Off Mode: mechanical type/contactless type
- Output Mode: OS2- 4-wire PNP/4-wire NPN/3-wire PNP
OS3- Multiple output/contactless
- Electrical Principle: refer the position indicator
- Wiring Method: Unscrew the transparent cover, thread the cable through the cable opening and connect it to the required terminal.

Y-type Angle Seat Valve

Order Instruction

101 Series
Pneumatic Angle
Seat Valve


Technical Specification

- Operating pressure: 0-10bar (0-145psi)
- Control pressure: 3-8bar (43.5-116psi)
- Control fluid: Filtered compressed air or neutral gas
- Cylinder material: CF8
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: PTFE
- Applicable medium: Water, Oil, Air, Liquid, Organic solvent, Acid and lye
- Medium temperature: -10°C — +180°C
- Ambient temperature: -10°C — +80°C
- Control type: Single acting normally closed,
Double acting normally closed,
Double acting without spring
- Connection type: Threaded, Welded, Tri-clamp, Flanged
- Leakage class: DIN EN 12266 Class A

Advantages


1. Lightweight appearance, compact structure, and excellent performance.
2. Y-shaped structure design of the valve body features high flow rate, low flow resistance, and rapid action response.
3. Stainless steel actuator, better performance for harsh environments

Y-type Angle Seat Valve



Main Dimension

Size	Actuator (mm)	Q	ΦC	R	K	Threaded connection				Welded connection							
						G	A	L	SW	HA	HL	Chamfer		DIN11850-2		DIN11850-3	
DN8	28	1/8"	42	21	105	1/4"	115	68	27	—	—	—	—	—	—	—	—
DN10	28	1/8"	42	21	105	3/8"	115	68	27	—	—	—	—	—	—	—	—
DN15	28	1/8"	42	21	105	1/2"	115	68	27	105	70	22	3.5	19	1.5	20	2
DN20	40	1/8"	50.5	27	130	3/4"	135	75	32	135	82	29	5	23	1.5	24	2
DN25	40	1/8"	50.5	27	135	1"	145	90	40	145	100	35	5	29	1.5	30	2
DN32	50	1/8"	60	33	165	1 1/4"	180	116	50	175	125	39	4	35	1.5	36	2
DN40	50	1/8"	60	33	170	1 1/2"	180	116	56	180	130	45	4.5	41	1.5	42	2
DN50	50	1/8"	60	33	175	2"	195	138	69	195	155	57	4	53	1.5	54	2



Main Dimension

Size	Tri-clamp connection (Chuck standard ISO 2852)						Flange connection (Flange standard JB/T 82.1)										
	KK	KA	KL	ΦC*	Φd*	D	FK	FA	FL	f	H	E	N-F	M	N	P	α
DN15	105	120	80	20.5	15	34	110	130	130	2	14	65	4-14	16	45	95	45°
DN20	135	145	130	25	19	50.5	135	155	150	2	14	75	4-14	19	56	105	45°
DN25	135	155	130	33	27	50.5	140	160	160	2	14	85	4-14	26	65	115	45°
DN32	160	185	146	37	31	50.5	175	180	180	2	16	100	4-18	31	78	140	45°
DN40	165	200	160	40	34	64	180	200	200	3	16	110	4-18	38	84	150	45°
DN50	180	210	175	53	45	64	185	230	230	3	16	125	4-18	54	100	165	45°

Note: * designates design dimension (the actual dimension may vary)

101 Series Pressure Parameter

Single Acting, Normally Closed (NC)
—Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	1.7	28	0-1.0	0.5-0.7
DN10	G3/8"	13	3.6	28	0-1.0	0.5-0.7
DN15	G1/2"	13	4.1	28	0-1.0	0.5-0.7
DN20	G3/4"	18	7.1	40	0-1.0	0.4-0.6
DN25	G1"	24	11.9	40	0-1.0	0.4-0.65
DN32	G1 1/4"	31	24.8	50	0-1.0	0.35-0.7
DN40	G1 1/2"	35	28.7	50	0-0.7	0.35-0.7
DN50	G2"	45	44.3	50	0-0.45	0.35-0.7

Single Acting, Normally Closed (NC)
—Enter Below Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	1.7	28	0-1.0	≥0.5
DN10	G3/8"	13	3.6	28	0-1.0	≥0.5
DN15	G1/2"	13	4.1	28	0-1.0	≥0.5
DN20	G3/4"	18	7.1	40	0-0.8	≥0.4
DN25	G1"	24	11.9	40	0-0.3	≥0.4
DN32	G1 1/4"	31	24.8	50	0-0.5	≥0.5
DN40	G1 1/2"	35	28.7	50	0-0.4	≥0.5
DN50	G2"	45	44.3	50	0-0.15	≥0.5

Double Acting, Normally Closed (NC)
—Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	1.7	28	0-1.0	0.5-0.7
DN10	G3/8"	13	3.6	28	0-1.0	0.5-0.7
DN15	G1/2"	13	4.1	28	0-1.0	0.5-0.7
DN20	G3/4"	18	7.1	40	0-1.0	0.4-0.6
DN25	G1"	24	11.9	40	0-1.0	0.4-0.65
DN32	G1 1/4"	31	24.8	50	0-1.0	0.35-0.7
DN40	G1 1/2"	35	28.7	50	0-0.7	0.35-0.7
DN50	G2"	45	44.3	50	0-0.45	0.35-0.7

Double Acting, Normally Closed (NC)
—Enter Below Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	1.7	28	0-1.0	0.5-0.7
DN10	G3/8"	13	3.6	28	0-1.0	0.5-0.7
DN15	G1/2"	13	4.1	28	0-1.0	0.5-0.7
DN20	G3/4"	18	7.1	40	0-1.0	0.4-0.5
DN25	G1"	24	11.9	40	0-1.0	0.4-0.5
DN32	G1 1/4"	31	24.8	50	0-1.0	0.35-0.6
DN40	G1 1/2"	35	28.7	50	0-1.0	0.35-0.6
DN50	G2"	45	44.3	50	0-0.45	0.35-0.7

Double Acting Without Spring
—Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	1.7	28	0-1.0	0.3-0.6
DN10	G3/8"	13	3.6	28	0-1.0	0.3-0.6
DN15	G1/2"	13	4.1	28	0-1.0	0.3-0.6
DN20	G3/4"	18	7.1	40	0-1.0	0.3-0.4
DN25	G1"	24	11.9	40	0-1.0	0.3-0.5
DN32	G1 1/4"	31	24.8	50	0-1.0	0.3-0.5
DN40	G1 1/2"	35	28.7	50	0-1.0	0.3-0.6
DN50	G2"	45	44.3	50	0-0.65	0.3-0.7


Double Acting Without Spring
—Enter Below Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	1.7	28	0-1.0	0.3-0.6
DN10	G3/8"	13	3.6	28	0-1.0	0.3-0.6
DN15	G1/2"	13	4.1	28	0-1.0	0.3-0.6
DN20	G3/4"	18	7.1	40	0-1.0	0.3-0.5
DN25	G1"	24	11.9	40	0-1.0	0.3-0.7
DN32	G1 1/4"	31	24.8	50	0-1.0	0.3-0.6
DN40	G1 1/2"	35	28.7	50	0-1.0	0.3-0.7
DN50	G2"	45	44.3	50	0-0.35	0.3-0.7


Note: In order to ensure product performance, it is recommended to select product according to the highest value in the ≤ 90% pressure range

Y-type Angle Seat Valve


Order Instruction



All the actuators except 28mm can be customized with accessory.

107 Series
Threaded Manual
Angle Seat Valve107 Series
Welded Manual
Angle Seat Valve

Threaded connection



Welded connection

Chamfer

Main Dimension

Size	C	K	Threaded connection							Welded connection					
			G	T	A	L	SW	HA	HL	Chamfer		DIN11850-2		DIN11850-3	
										Φ D*	S*	Φ D	S	Φ D	S
DN8	62	115	1/4"	12	128	68	27	-	-	-	-	-	-	-	-
DN10	62	115	3/8"	12	128	68	27	-	-	-	-	-	-	-	-
DN15	62	115	1/2"	15	128	68	27	120	70	22	3.5	19	1.5	20	2
DN20	62	120	3/4"	16	133	75	32	128	82	29	5	23	1.5	24	2
DN25	62	125	1"	17	142	90	40	144	100	35	5	29	1.5	30	2
DN32	62	146	1 1/4"	21	166	116	50	165	125	39	4	35	1.5	36	2
DN40	62	148	1 1/2"	21	168	116	56	168	130	45	4.5	41	1.5	42	2
DN50	62	155	2"	22	182	138	69	182	155	57	4	53	1.5	54	2
DN65 Square bonnet	80	211	2 1/2"	26	226	178	85	270	270	75	5	70	2		

Note: * designates design dimension (the actual dimension may vary)




Y-type Angle Seat Valve


107 Series
Tri-clamp Manual
Angle Seat Valve



107 Series
Flanged Manual
Angle Seat Valve



Tri-clamp connection




Flange connection

Main Dimension

Size	C	Tri-clamp connection				Flange connection										
		K	ΦD	L	A	K	A	L	C	H	ΦE	n-ΦF	ΦM	ΦN	ΦP	α
DN15	62	113	34	80	132	116	136	130	2	14	65	4-14	16	45	95	45°
DN20	62	122	50.5	130	147	122	157	150	2	14	75	4-14	19	56	105	45°
DN25	62	126	50.5	130	156	127	157	160	2	14	85	4-14	26	65	115	45°
DN32	62	142	50.5	146	174	147	162	180	2	16	100	4-18	31	78	140	45°
DN40	62	141	64	160	185	149	181	200	3	16	110	4-18	38	84	150	45°
DN50	62	152	64	175	195	156	210	230	3	16	125	4-18	54	100	165	45°
DN65 Square bonnet	80	200	91	278	266	201	272	290	3	18	145	4-18	71	120	185	45°

Technical Specification

- Operating pressure: 0-16bar (0-232psi)
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: PTFE
- Applicable medium: Water, Alcohol, Oil, Fuel, Steam, Neutral gas or Liquid, organic solvent, weak acid or weak base solution
- Fluid temperature: -10°C — +180°C
+25°C — +220°C
- Ambient temperature: -10°C — +80°C
- Maximum fluid viscosity: 600m²/s
- Connection type: Threaded, Welded, Tri-clamp, Flange
- Leakage class: DIN EN 12266 Class A



Adjustable seat

Note: Adjustable seat can be installed to achieve manual flow adjustment.

Order Instruction

107

XXX

X

XX

X

X

(*)

Series No.

D08、D10、D15、
Size D20、D25、D32、
D40、D50、D65

Installation direction
Y: Above seat
W: Below seat

Customization
E: Complying with EC1935
*: Special customization

Sealing material
2: PTFE Normal temperature
3: PTFE High temperature
4: Graphite Normal temperature
5: Graphite High temperature
*: Customized sealing

Body Material
1: CF8
2: CF8M
6: CF3M

Connection type
G1: Threaded BSP DIN ISO 228-1
T1: Threaded BSPT DIN 2999-1/ISO7-1
N1: Threaded NPT ASME B1.20.1
H7: Welded DIN11850-2/DIN11866 A
H8: Welded DIN11850-3
H9: Welded Chamfer
H*: Welded customized dimension
K7: Tri-clamp ISO2852
K*: Tri-clamp customized dimension
F2: Flange JB/T82
(DIN2543/DIN2576/EN1092-1/HG20592)
F*: Flange customized dimension

Y-type Angle Seat Valve

120 Series
Threaded Pneumatic
Angle Seat Valve120 Series
Welded Pneumatic
Angle Seat Valve120 Series
Tri-clamp Pneumatic
Angle Seat Valve120 Series
Flanged Pneumatic
Angle Seat Valve


Technical Specification

- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: PTFE
- Actuator material: CF8 (28mm–90mm Actuator), AL (125mm Actuator)
- Actuator size: 28mm, 40mm, 50mm, 63mm, 90mm, 125mm
- Applicable fluid: Water, Alcohol, Oil, Fuel, Steam, Neutral gas or Liquid, Organic solvent, Acid and lye
- Fluid viscosity: Max 600mm²/s
- Fluid temperature: –10°C — +180°C, +25°C — +220°C
- Ambient temperature: –10°C — +80°C
- Control type: Single acting normally closed, Single acting normally open, Double acting normally closed, Double acting without spring
- Connection type: Threaded (BSP, BSPT, NPT), Welded, Tri-clamp, Flanged

Advantages


1. New sealing structure can reduce residues and be easy to clean.
2. High flow rate, low flow resistance, and no water hammer.
3. Y-shaped valve body design, increasing flow by 30%.
4. Ultra long service life.
5. Valve rod auto-correction and self-lubricating.
6. Stainless steel actuator, better performance in harsh environment

Order Instruction




All the actuators except 28mm can be customized with accessory.

Y-type Angle Seat Valve



Threaded Connection




Welded Connection

Main Dimension (Threaded Connection)


Size	Actuator (mm)	Q	ΦC	R	K	A	Kv (m³/h)	G	T	L	SW
DN8	28	1/8"	42	21	110	117	1.8	1/4"	12	65	27
	40	1/8"	50.5	27	125	131	2.2				
	50	1/8"	60	33	139	143	2.2				
DN10	28	1/8"	42	20	110	117	2	3/8"	14	65	27
	40	1/8"	50.5	27	125	131	3.9				
	50	1/8"	60	33	139	143	3.9				
DN15	28	1/8"	42	20	110	117	2.2	1/2"	16	65	27
	40	1/8"	50.5	27	125	131	4.3				
	50	1/8"	60	33	139	143	4.3				
DN20	50	1/8"	60	33	141	146	7.6	3/4"	18	75	32
DN25	50	1/8"	60	33	145	155	15.8	1"	20	90	40
	63	1/8"	75	41	167	177					
DN32	63	1/8"	75	41	180	193	26.0	1 1/4"	22	110	50
	90	1/8"	106	55	227	235					
DN40	63	1/8"	75	41	180	197	32.0	1 1/2"	24	120	56
	90	1/8"	106	55	228	239					
DN50	63	1/8"	75	41	187	215	52.0	2"	26	150	69
	90	1/8"	106	55	235	258					
	125AL	1/4"	170	85	300	312					

Main Dimension (Welded Connection)

Size	Actuator (mm)	Q	ΦC	R	K	A	Kv (m³/h)	L	H	ASME BPE	
										ΦD	S
DN15	28	1/8"	42	21	112	143	1.3	135	30	12.7	1.65
	40	1/8"	50.5	27	127	155	1.7				
	50	1/8"	60	33	140	166	1.7				
DN20	50	1/8"	60	33	138	170	5.8	145	30	19.05	1.65
DN25	50	1/8"	60	33	146	176	11.8	152	30	25.4	1.65
	63	1/8"	75	41	168	200					
DN40	63	1/8"	75	41	177	216	20.6	182	30	38.1	1.65
	90	1/8"	106	55	225	258					
DN50	63	1/8"	75	41	187	228	55.7	210	30	50.8	1.65
	90	1/8"	106	55	235	270					
DN65 Square bonnet	125AL	1/4"	170	85	300	325	71.6	230	26	63.5	1.65
DN80 Square bonnet	125AL	1/4"	170	85	355	380					



Tri-clamp Connection



Flange connection

Main Dimension (Tri-clamp Connection)

Size	Actuator (mm)	Q	ΦC	R	K	A	Kv (m³/h)	L	ASME BPE			
									ΦD	ΦB	Φd	H
DN15	28	1/8"	42	21	112	145	1.3	130	25	12.7	9.4	30
	40	1/8"	50.5	27	127	158	1.7					
	50	1/8"	60	33	140	169	1.7					
DN20	50	1/8"	60	33	138	172	5.8	150	25	19.05	15.75	30
DN25	50	1/8"	60	33	146	180	11.8	160	50.5	25.4	22.1	30
	63	1/8"	75	41	169	205						
DN40	63	1/8"	75	41	177	225	20.6	200	50.5	38.1	34.8	30
	90	1/8"	106	55	225	267						
DN50	63	1/8"	75	41	187	238	55.7	230	64	50.8	47.5	30
	90	1/8"	106	55	235	280						
	125AL	1/4"	170	85	300	335						
DN65 Square bonnet	90	1/8"	106	55	286	327	71.6	290	77.4	63.5	60.2	26
	125AL	1/4"	170	85	337	368						
DN80 Square bonnet	125AL	1/4"	170	85	349	383	105.2	315	91	76.2	72.9	26

Main Dimension (Flange Connection)

Size	Actuator (mm)	Q	A	B	Kv (m³/h)	L	C	H	ΦE	n-ΦF	ΦM	ΦN	ΦP	α
DN15 Square bonnet	40	1/8"	135	125	4.3	130	2	14	65	4-14	16	45	95	45°
	50		145	140										
DN20 Square bonnet	50	1/8"	165	140	7.6	150	2	14	75	4-14	19	56	105	45°
	50		170	145										
DN25 Square bonnet	63	1/8"	190	175	15.8	160	2	14	85	4-14	26	65	115	45°
	63		190	188										
DN32 Square bonnet	90	1/8"	230	235	26.0	180	2	16	100	4-18	31	78	140	45°
	90		206	190										
DN40 Square bonnet	63	1/8"	206	190	32.0	200	3	16	110	4-18	38	84	150	45°
	90		250	240										
DN50 Square bonnet	63	1/8"	235	195	52.0	230	3	16	125	4-18	54	100	165	45°
	90		277	245										
	125AL		330	210										

Flange specification: JB/T82.1(DIN2543/DIN2576/EN1092-1/HG20592); ISO/DIN/JIS customization available



Y-type Angle Seat Valve

121 Series
Angle Diaphragm Valve



Technical Specification


- Operating pressure: 0–10bar (0–145psi)
- Control pressure: 4–8bar (58–116psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: PTFE
- Actuator material: CF8
- Actuator size: 40mm, 50mm, 63mm, 90mm
- Applicable fluid: Water, Oil, Neutral gas or Liquid, Organic solvent, Acid and lye
- Fluid temperature: –10°C — +150°C
- Ambient temperature: –10°C — +80°C
- Control type: Single acting normally closed, Double acting normally closed
- Connection type: Threaded, Welded, Tri-clamp,

Advantages


- Diaphragm is used to isolate the medium, avoiding valve stem from seizing due to medium crystallization or being viscous with particles.
- Stainless steel actuator, better performance for harsh environments

Function Principle

Diaphragm is arranged between the valve body and the bonnet to isolate the medium in place of the stem packing. Valve stays closed(open) by spring force in its normal state. When piston is actuated by compressed air, valve becomes opened (close). For double acting type, valve is opened and closed by compressed



Threaded Connection



Welded Connection


Main Dimension (Threaded Connection)

Size	Actuator (mm)	Q	C	R	K	A	G	T	L	SW
DN15	40	1/8"	50.5	27	115	125	1/2"	16	65	27
DN20	50	1/8"	60	33	130	140	3/4"	18	75	32
DN25	50	1/8"	60	33	140	150	1"	20	90	40
	63	1/8"	75	41	155	165				
DN32	63	1/8"	75	41	170	185	1 1/4"	22	110	50
	90	1/8"	106	55	215	225				
DN40	63	1/8"	75	41	180	195	1 1/2"	24	120	56
	90	1/8"	106	55	220	230				
DN50	63	1/8"	75	41	180	210	2"	26	150	69
	90	1/8"	106	55	230	255				

Main Dimension (Welded Connection)

Size	Actuator (mm)	Q	C	R	K	A	L	H	ASME BPE	
									ΦD	S
DN15	40	1/8"	50.5	27	115	150	135	30	12.7	1.65
DN20	50	1/8"	60	33	130	165	145	30	19.05	1.65
DN25	50	1/8"	60	33	140	175	152	30	25.4	1.65
	63	1/8"	75	41	155	190				
DN40	63	1/8"	75	41	175	215	182	30	38.1	1.65
	90	1/8"	106	55	215	250				
DN50	63	1/8"	75	41	180	225	210	30	50.8	1.65
	90	1/8"	106	55	225	265				

Y-type Angle Seat Valve



Tri-clamp Connection

Main Dimension (Tri-clamp Connection)

Size	Actuator (mm)	Q	C	R	K	A	L	ASME BPE			
								ΦD	ΦB	Φd	H
DN15	40	1/8"	50.5	27	115	150	130	25	12.7	9.4	30
DN20	50	1/8"	60	33	125	165	150	25	19.05	15.75	30
DN25	50	1/8"	60	33	140	175	160	50.5	25.4	22.1	30
	63	1/8"	75	41	155	195					
DN40	63	1/8"	75	41	175	225	200	50.5	38.1	34.8	30
	90	1/8"	106	55	215	230					
DN50	63	1/8"	75	41	180	230	230	64	50.8	47.5	30
	90	1/8"	106	55	225	275					

Single Acting, Normally Closed (NC)
-Enter Below Seat (Minimize water-hammer)



Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN15	1/2"	13	3	40	0-1.0	≥0.5
DN20	3/4"	18	5.8	50	0-1.0	≥0.5
DN25	1"	24	11.6	50	0-0.7	≥0.5
				63	0-1.0	≥0.6
DN32	1 1/4"	31	17.3	63	0-0.6	≥0.6
				90	0-1.0	≥0.5
DN40	1 1/2"	35	22.7	63	0-0.5	≥0.55
				90	0-1.0	≥0.75
DN50	2"	45	35.6	63	0-0.2	≥0.6
				90	0-1.0	≥0.75

Double Acting, Normally Closed (NC)
-Enter Below Seat (Minimize water-hammer)

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN15	1/2"	13	3	40	0-1.0	≥0.5
DN20	3/4"	18	5.8	50	0-1.0	≥0.45
DN25	1"	24	11.6	50	0-1.0	≥0.45
				63	0-1.0	≥0.4
DN32	1 1/4"	31	17.3	63	0-1.0	≥0.4
				90	0-1.0	≥0.35
DN40	1 1/2"	35	22.7	63	0-1.0	0.4-0.5
				90	0-1.0	0.3-0.4
DN50	2"	45	35.6	63	0-1.0	0.4-0.7
				90	0-1.0	0.3-0.4


Note: In order to ensure product performance, it is recommended to select product according to the highest value in the ≤ 90% pressure range

Order Instruction



Y-type Angle Seat Valve

122 Series
Pneumatic Angle
Stop Valve



Technical Specification

- Operating pressure: 0–10bar (0–145psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control fluid: Filtered compressed air or neutral gas
- Actuator material: CF8 (40mm–90mm Actuator), AL (125mm Actuator)
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: EPDM/FPM
- Applicable fluid: Vacuum and Inert gas, Dusty gas, Water, Oil, Steam, Liquid, Organic solvent, Acid and lye
- Fluid temperature: –10°C — +150°C
- Ambient temperature: –10°C — +80°C
- Control type: Single acting normally closed, Double acting normally closed, Double acting without spring
- Connection type: KF
- Valve seat leakage Pa · m³/s (He): below 1.3×10^{-10}




Main Dimension (KF)

Size	Actuator (mm)	Q	D	K	C	A	ΦB
DN16	40	1/8"	50.5	182	67	40	30
DN25	40	1/8"	50.5	194	77	50	40
DN40	50	1/8"	60	245	100	65	55
DN50	50	1/8"	60	255	105	70	75
DN63	90	1/8"	106	375	145	88	87
DN80	125	1/4"	170	440	175	90	114

Advantages

1. Lightweight appearance, compact structure, and excellent performance.
2. Stainless steel actuator, better performance for harsh environments and can rotate 360°.
3. Unique sealing structure design, applicable to dusty conditions,

Order Instruction





Y-type Angle Seat Valve

127 Series
Threaded Manual
Angle Seat Valve



127 Series
Welded Manual
Angle Seat Valve




Technical Specification

- Operating pressure: 0–16bar (0–232psi)
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: PTFE
- Applicable fluid: Water, Alcohol, Oil, Fuel, Steam, Neutral gas or Liquid, Organic solvent, Acid and lye
- Fluid temperature: –10°C — +180°C
+25°C — +220°C
- Ambient temperature: –10°C — +80°C
- Fluid viscosity: Max 600mm²/s
- Connection type: Threaded, Welded ASME–BPE, Tri-clamp ASME–BPE, Flange

Advantages

- New body seal design can reduce residue and easy to clean.
- Large flux, low resistance, no water–hammer.
- Y type raises flux by 30% and make smooth flow.
- The adjustable seat is optional to realize the adjustable flow by



Adjustable seat

Note: Adjustable seat can be installed to achieve manual flow adjustment.


127 Series
Tri-clamp Manual
Angle Seat Valve




127 Series
Flanged Manual
Angle Seat Valve



Order Instruction



Y-type Angle Seat Valve




Main Dimension (Threaded Connection)

Size	C	H	K	G	T	L	SW
DN8	62	130	117	1/4	12	65	27
DN10	62	130	117	3/8	14	65	27
DN15	62	130	117	1/2	16	65	27
DN20	62	133	119	3/4	18	75	32
DN25	62	141	125	1	20	90	40
DN32	62	162	143	1 1/4	22	110	50
DN40	62	167	143	1 1/2	24	120	56
DN50	62	185	150	2	26	150	69

Main Dimension (Welded Connection)

Size	C	H	K	L1	L	ASME BPE	
						ΦD	S
DN15	62	153	119	30	135	12.7	1.65
DN20	62	157	116	30	145	19.05	1.65
DN25	62	163	125	30	152	25.4	1.65
DN40	62	186	140	30	182	38.1	1.65
DN50	62	198	150	30	210	50.8	1.65
DN65 Square bonnet	80	235	200	26	230	63.5	1.65



Main Dimension (Tri-clamp Connection)

Size	C	H	K	L1	L	ASME BPE		
						ΦD	ΦB	Φd
DN15	62	156	119	30	130	25	12.7	9.4
DN20	62	159	116	30	150	25	19.05	15.75
DN25	62	167	125	30	160	50.5	25.4	22.1
DN40	62	195	140	30	200	50.5	38.1	34.8
DN50	62	208	150	30	230	64	50.8	47.5
DN65 Square bonnet	80	265	200	26	290	77.4	63.5	60.2

Main Dimension (Flanged Connection)

Size	C	K	A	L	H1	H	ΦE	n-ΦF	ΦM	ΦN	ΦP	α
DN15 Square bonnet	62	116	136	130	2	14	65	4-14	16	45	95	45°
DN20 Square bonnet	62	122	157	150	2	14	75	4-14	19	56	105	45°
DN25 Square bonnet	62	127	157	160	2	14	85	4-14	26	65	115	45°
DN32 Square bonnet	62	147	162	180	2	16	100	4-18	31	78	140	45°
DN40 Square bonnet	62	149	181	200	3	16	110	4-18	38	84	150	45°
DN50 Square bonnet	62	156	210	230	3	16	125	4-18	54	100	165	45°



Proportional Control Angle Seat Valve

104 Series
Two-piece Pneumatic
Proportional Control
Angle Seat Valve




Technical Specification

- Connection type: Threaded, Welded, Tri-clamp, Flange
- Medium temperature: -10°C — +180°C
+25°C — +220°C
- Medium temperature: 0 — +60°C
- Operating pressure: Refer to the selection table of proportional adjustment angle seat valve
- Control pressure: 3—7bar (43.5—102psi)
- Control power: 24VDC ± 10%
- Valve set signal: 0/4—20mA or 0—5/10V
- Power consumption: <4W
- Input Signal Impedance: 120Ω at 0/4—20mA,
40KΩ under 0—5/10V
- Simulated Output signal: Max load is 750Ω at 0/4—20mA,
Max current is 20mA under 0—5/10V3
- Maximum current of digital signal output: 100mA
- Protection: IP65
- Explosion-proof: II 3G Ex ec IIC T4 Gc
- Leakage class: DIN EN 12266 Class A

Advantages


- Convenient to adjust and easy to operate.
- Stable operation with vibration resistance.
- The unique design of adjustable seat establishes a proportional linear relationship between open/close state of the valve with the flow rate, achieving precise flow adjustment.
- For 104 and 124 series, the intelligent positioner and the valve are separate and can be installed at a distance, making it more suitable for high temperature and humidity environment.
- No air consumption when in steady state.

Order Instruction




Proportional Control Angle Seat Valve

105 Series
Pneumatic Proportional
Control Angle Seat Valve



Order Instruction

105	XXX	X	XXX	X	XX	X	X	X	X	(*)	XXX
Series No.											
Actuator	A50、A63、A90、125										
Control type	0: Normally open 1: Single acting normally closed										
Size	D04、D06、D08、D10、D15、D20、D25、D32、D40、D50、D65、D80、100										
Installation direction	Y: Above seat W: Below seat										
Connection type	G1: Threaded BSP DIN ISO 228-1 T1: Threaded BSPT DIN 2999-1/ISO7-1 N1: Threaded NPT ASME B1.20.1 H7: Welded DIN11850-2/DIN11866 A H8: Welded DIN11850-3 H9: Welded Chamfer H*: Welded customized dimension K7: Tri-clamp ISO2852 K*: Tri-clamp customized dimension F2: Flange JB/T82 (DIN2543/DIN2576/EN1092-1/HG20592) F*: Flange customized dimension										
Sealing material	2: PTFE Normal temperature 3: PTFE High temperature 4: Graphite Normal temperature 5: Graphite High temperature *: Customized sealing										
Spring selection	A: Spring A B: Spring B										
Actuator material	1: CF8 8: AL (AL only applicable for 125 actuator)										
Body material	1: CF8 2: CF8M 6: CF3M										



105 Series Main Dimension (Threaded Connection)

Size	Actuator (mm)	Q	K	A	L	G	SW	T
DN4	50	1/8"	224	221	68	1/2" 3/8"	27	12
DN6	50	1/8"	224	221	68	1/2" 3/8"	27	12
DN8	50	1/8"	224	221	68	1/4"	27	12
	63	1/8"	237	233				
DN10	50	1/8"	224	221	68	3/8"	27	12
	63	1/8"	237	233				
DN15	50	1/8"	224	221	68	1/2"	27	15
	63	1/8"	237	233				
DN20	50	1/8"	231	226	75	3/4"	32	16
	63	1/8"	244	237				
DN25	50	1/8"	235	236	90	1"	40	17
	63	1/8"	257	253				
DN32	63	1/8"	269	271	116	1 1/4"	50	21
	90	1/8"	319	301				
DN40	90	1/8"	319	301	116	1 1/2"	56	21
DN50	90	1/8"	328	316	138	2"	69	22
	125AL	1/4"	386	359				
DN65 Square bonnet	125AL	1/4"	416	374	178	2 1/2"	85	26
DN80 Square bonnet	125AL	1/4"	441	394	210	3"	100	27


105 Series Main Dimension (Welded Connection)

Size	Actuator (mm)	Q	K	HA	HL	Chamfer		DIN11850-2		DIN11850-3	
						ΦD*	S*	ΦD	S	ΦD	S
DN15	50	1/8"	224	214	70	22	3.5	19	1.5	20	2
	63	1/8"	237	226							
DN20	50	1/8"	231	221	82	29	5	23	1.5	24	2
	63	1/8"	244	232							
DN25	50	1/8"	235	236	100	35	5	29	1.5	30	2
	63	1/8"	257	256							
DN32	63	1/8"	269	267	125	39	4	35	1.5	36	2
	90	1/8"	319	298							
DN40	90	1/8"	319	301	130	45	4.5	41	1.5	42	2
DN50	90	1/8"	318	316	155	57	4	53	1.5	54	2
	125AL	1/4"	386	361							
DN65 Square bonnet	125AL	1/4"	416	414	270	75	5	70	2	—	—
DN80 Square bonnet	125AL	1/4"	441	414	284	90	5.5	85	2	—	—

Note: * Designates design dimension (the actual dimension may vary)



Proportional Control Angle Seat Valve




105 Series Main Dimension (Tri-clamp Connection)

Size	Actuator (mm)	Q	K	A	L	ΦC	ΦD	Φd
DN15	50	1/8"	221	221	80	20.5	34	15
DN20	50	1/8"	243	239	130	25	50.5	19
	63	1/8"	258	256				
DN25	50	1/8"	239	251	130	33	50.5	27
	63	1/8"	261	269				
DN32	63	1/8"	269	281	146	37	50.5	31
	90	1/8"	319	311				
DN40	90	1/8"	319	321	160	40	64	34
DN50	90	1/8"	331	331	175	53	64	45
	125AL	1/4"	382	379				
DN65 Square bonnet	125AL	1/4"	416	414	278	75	91	65
DN80 Square bonnet	125AL	1/4"	438	414	290	89.5	106	78.5

105 Series Main Dimension (Flange Connection)

Size	Actuator (mm)	Q	K	A	L	ΦP	ΦN	ΦM	H	C	ΦE	n-ΦF
DN15	50	1/8"	237	232	130	95	45	16	14	2	65	4-14
DN20	50	1/8"	237	252	150	105	56	19	14	2	75	4-14
DN25	50	1/8"	267	257	160	115	65	26	14	2	85	4-14
	63	1/8"	268	272								
DN32	63	1/8"	281	272	180	140	78	31	16	2	100	4-18
	90	1/8"	329	297								
DN40	90	1/8"	334	317	200	150	84	38	16	3	110	4-18
DN50	90	1/8"	339	344	230	165	100	54	16	3	125	4-18
	125AL	1/4"	394	385								
DN65 Square bonnet	125AL	1/4"	414	430	290	185	120	71	18	3	145	4-18
DN80 Square bonnet	125AL	1/4"	439	435	310	200	135	84	20	3	160	8-18
DN100 Square bonnet	125AL	1/4"	467	482	350	215	155	96	20	3	180	8-18

106 Series
Electrical Proportional
Control Angle Seat Valve



Technical Specification

- Voltage: 220V AC or 24V AC
- Control Power: 4-20mA or 0-10V DC
- Ambient Temperature: -15°C — +50°C
- Connection type: Threaded, Welded, Flange, Tri-clamp
- Positioner: Electrical motor control
- Protection: IP54
- Leakage class: DIN EN 12266 Class A

Advantages

- 1. Convenient and easy to use.

Function Principle

Electrical positioner controls the angle seat valve's open/close state through 4-20 mA or 0-10V DC signals. It achieves precise flow adjustment using the adjustable seat within the valve and may allow

Attention

- If the valve body needs to be taken off during installation, please recalibrate the zero-point. Keep the positioner upright at all time.
- To ensure accurate adjustment, please install the valve in below seat direction.
-




Proportional Control Angle Seat Valve

Pressure Data Sheet

Size	Orifice	Actuator	Pressure range (enter below seat) MPa	Pressure range (enter above seat) MPa
DN15	13	10P	0-1.6	0-1.6
DN20	18	10P	0-1.6	0-1.6
DN25	24	10P	0-1.2	0-1.6
		20P	0-1.6	0-1.6
DN32	31	10P	0-0.5	0-1.2
		20P	0-1.6	0-1.6
DN40	35	10P	0-0.3	0-0.9
		20P	0-1.4	0-1.6
		35P	0-1.6	0-1.6
DN50	45	10P	-	0-0.5
		20P	0-0.6	0-1.1
		35P	0-1.5	0-1.6
DN65	61	20P	-	0-0.6
		35P	0-0.7	0-1.1
DN80	80	20P	-	0-0.3
		35P	0-0.3	0-0.6
DN100	90	35P	-	0-0.4

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Order Instruction



124 Series
Two-piece Pneumatic
Proportional Control
Angle Seat Valve



Function Principle


Positioner receives 0/4-20mA(0-5/10V) electrical signals from control system and converts them into air signals to control the



Control Output Chart

By selecting characteristic curve of the positioner, the controlled valve can output to straight-line, equal-percentage, quick-

Attention


- Ensure that the inlet pressure of P port is sufficient and has been opened.
- Ensure that there is no leakage in the air supply pipeline, especially when there are changes in the air supply.
- Ensure that the power supply wiring is correct.
- Ensure that the signal source input mode matches and there is no interference.
- Ensure that the contro valve takes protective measures to avoid water droplets and causing disfunction in operation panel.
- While installation, if the valve body needs to be removed, please adjust to the zero point again after installation.
- It is recommended that the signal to be 4-20mA to reduce the interference when signal value is low.
- It is recommended to use shielding wire for the signal line.








Proportional Control Angle Seat Valve



125 Series Threaded connection




125 Series Welded connection

125 Series Main Dimension (Threaded connection)


Size	Actuator (mm)	Q	K	A	L	G	SW	T
DN8	50	1/8"	229	224	65	1/4"	27	12
	63	1/8"	244	236				
DN10	50	1/8"	229	224	65	3/8"	27	14
	63	1/8"	244	236				
DN15	50	1/8"	229	224	65	1/2"	27	16
	63	1/8"	244	236				
DN20	50	1/8"	232	229	75	3/4"	32	18
	63	1/8"	246	239				
DN25	50	1/8"	235	235	90	1"	40	20
	63	1/8"	259	254				
DN32	63	1/8"	270	271	110	1 1/4"	50	22
	90	1/8"	312	304				
DN40	90	1/8"	312	308	120	1 1/2"	56	24
	90	1/8"	319	326				
DN50	90	1/8"	319	326	150	2	69	26
	125AL	1/4"	374	372				

125 Series Main Dimension (Welded connection)

Size	Actuator (mm)	Q	K	A	L	H	ASME BPE	
							ΦD	S
DN15	50	1/8"	230	247	135	30	12.7	1.65
	63	1/8"	246	259				
DN20	50	1/8"	229	251	145	30	19.05	1.65
	63	1/8"	242	264				
DN25	50	1/8"	236	258	152	30	25.4	1.65
	63	1/8"	259	276				
DN40	90	1/8"	309	329	182	30	38.1	1.65
DN50	90	1/8"	319	339	210	30	50.8	1.65
	125AL	1/4"	374	386				
DN65 Square bonnet	125AL	1/4"	417	386	230	26	63.5	1.65
DN80 Square bonnet	125AL	1/4"	436	436	310	26	76.2	1.65



125 Series Tri-clamp connection



125 Series Flanged connection

125 Series Main Dimension (Tri-clamp connection)

Size	Actuator (mm)	Q	K	A	L	ASME BPE			
						D	B	d	H
DN15	50	1/8"	230	251	130	25	12.7	9.4	30
	63	1/8"	246	262					
DN20	50	1/8"	229	254	150	25	19.05	15.75	30
	63	1/8"	244	263					
DN25	50	1/8"	236	261	160	50.5	25.4	22.1	30
	63	1/8"	259	281					
DN40	90	1/8"	309	336	200	50.5	38.1	34.8	30
DN50	90	1/8"	319	351	230	64	50.8	47.5	30
	125AL	1/4"	374	396					
DN65 Square bonnet	125AL	1/4"	417	416	290	77.4	63.5	60.2	26
DN80 Square bonnet	125AL	1/4"	439	437	315	91	76.2	72.9	26

125 Series Main Dimension (Flanged connection)

Size	Actuator (mm)	Q	K	A	L	ΦP	ΦN	ΦM	H	C	ΦE	n-ΦF
DN15	50	1/8"	237	232	130	95	45	16	14	2	65	4-14
DN20	50	1/8"	237	252	150	105	56	19	14	2	75	4-14
DN25	50	1/8"	267	257	160	115	65	26	14	2	85	4-14
	63	1/8"	268	272								
DN32	63	1/8"	281	272	180	140	78	31	16	2	100	4-18
	90	1/8"	329	297								
DN40	90	1/8"	327	307	200	150	84	38	16	3	110	4-18
DN50	90	1/8"	334	336	230	165	100	54	16	3	125	4-18
	125AL	1/4"	394	385								



Proportional Control Angle Seat Valve

Single Acting, Normally closed (NC) -Enter Below Seat

Size	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range ΔP(MPa)	Control pressure (MPa)
DN4	4	0.52	50A	0-1.6	≥0.45
DN6	6	1.1	50A	0-1.6	≥0.45
DN8	13	2.2	50A	0-1.4	≥0.45
			63A	0-1.6	≥0.50
			63B	0-1.6	≥0.30
DN10	13	3.3	50A	0-1.4	≥0.45
			63A	0-1.6	≥0.50
			63B	0-1.6	≥0.30
DN15	13	3.3	50A	0-1.4	≥0.45
			63A	0-1.6	≥0.50
			63B	0-1.6	≥0.30
DN20	18	6.7	50A	0-1.4	≥0.45
			63A	0-1.6	≥0.50
			63B	0-1.6	≥0.30
DN25	24	11.4	50A	0-0.8	≥0.45
			63A	0-1.3	≥0.50
			63B	0-0.7	≥0.30
DN32	31	18.3	63A	0-0.6	≥0.50
			90B	0-1.3	≥0.45
DN40	35	24.5	63A	0-0.5	≥0.50
			90A	0-1.6	≥0.60
			90B	0-1.1	≥0.45
DN50	45	40.4	90A	0-1.0	≥0.60
			90B	0-0.7	≥0.45
			125A	0-1.6	≥0.55
			125B	0-1.1	≥0.45
DN65	61	46.8	90A	0-0.5	≥0.60
			125A	0-0.9	≥0.55
			125B	0-0.6	≥0.45
DN80	80	84.0	125A	0-0.5	≥0.55

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Single Acting, Normally Closed (NC)-Enter Above Seat
(Please pay attention to the selection of spring. 6325, 6332 and 6340 need a customized positioner.)

Size	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range ΔP(MPa)	Control pressure (MPa)
DN15	13	3.3	50A	0-1.6	≥0.45
			63B	0-1.6	≥0.30
DN20	18	6.7	50A	0-1.6	0.45-0.55
			63B	0-1.6	0.30-0.40
DN25	24	11.4	63B	0-1.6	0.30-0.45
DN32	31	18.3	63B	0-1.6	0.30-0.60
			90B	0-1.6	≥0.45
DN40	35	24.5	63B	0-1.6	0.30-0.70
			90B	0-1.6	0.45-0.50
DN50	45	40.4	90B	0-1.6	0.45-0.70
			125A	0-1.6	0.30-0.35
DN65	61	46.8	90B	0-0.9	0.45-0.70
			125A	0-1.6	0.30-0.55
DN80	80	84.0	125A	0-1.2	0.30-0.70
DN100	90	95.0	125A	0-1.0	0.30-0.70

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Single Acting, Normally Open(NO)-Enter below Seat

Size	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range ΔP(MPa)	Control pressure (MPa)
DN15	13	3.3	50K	0-1.6	0.30-0.40
DN20	18	6.7	50K	0-1.6	0.30-0.50
DN25	24	11.4	50K	0-1.3	0.30-0.60
			63K	0-1.6	0.30-0.50
DN32	31	18.3	63K	0-1.3	0.30-0.60
DN40	35	21.3	90K	0-1.6	0.30-0.40
DN50	45	40.4	90K	0-1.6	0.30-0.55
DN65	61	46.8	90K	0-1.0	0.30-0.70
			125K	0-1.6	0.30-0.65
DN80	80	84.0	125K	0-1.0	0.30-0.70

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Opening (%) - Kv value (m³/h) chart of proportional angle seat valve

Size	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
DN4	0.02	0.04	0.07	0.11	0.14	0.19	0.26	0.35	0.43	0.52
DN6	0.04	0.08	0.14	0.22	0.33	0.43	0.57	0.75	0.93	1.1
DN8	0.53	0.83	1.14	1.53	1.91	2.2	2.2	2.2	2.2	2.2
DN10	0.53	0.83	1.14	1.53	1.91	2.26	2.58	2.84	3.05	3.3
DN15	0.53	0.83	1.14	1.53	1.91	2.26	2.58	2.84	3.05	3.3
DN20	1.48	2	2.57	3.27	4.16	5.06	5.65	6.08	6.43	6.7
DN25	1.37	2.98	4.39	5.94	7.14	8.27	9.03	9.98	10.82	11.4
DN32	3.79	6.74	9.07	11.17	12.12	13.36	15.35	16.37	17.63	18.3
DN40	3.78	6.85	9.39	12.44	15.4	17.46	20.55	22.02	23.54	24.5
DN50	8.64	15.49	21.67	27.02	29.98	32.93	35.45	37.38	39.52	40.4
DN65	7.53	11.34	15.31	17.83	19.4	21.84	27.3	33.4	40.54	46.8
DN80	9.84	11.18	16.53	22.66	29.82	35.73	48.37	60.21	70.69	84
DN100	12.54	14.56	25.32	36.75	45.6	54.38	62.5	72.8	84.23	95



Proportional Control Angle Seat Valve

135 Series
Micro Flow Control Valve




Technical Specification

- Operating pressure: 0–10bar (0–145psi)
- Control pressure: 3–7bar (43.5–102psi)
- Seal material: PTFE
- Applicable fluid: Water, Neutral gas or Liquid, Organic solvent, Acid and lye
- Fluid temperature: –10°C — +150°C
- Ambient temperature: –10°C — +60°C
- Control type: Single acting normally closed

Advantages


Bellows are used to isolate the medium and meet the requirements

Order Instruction




Function Principle

Positioner receives 0/4–20mA(0–5/10v) electrical signals from control system and converts them into air signals to control the valve and make precise low adjustment using the bellow adjustable seat. Diaphragm is arranged between the valve body and the bonnet to isolate the medium in place of the stem packing. Valve stays closed(open) by spring force in its normal state. When piston is actuated by compressed air, valve becomes opened



Welded connection



Tri-clamp connection

135 Series Main Dimension
(Welded connection)

Size	Actuator (mm)	K	L	H	ASME BPE	
					D	S
DN1.5/3/6	50	275	90	16	12.7	1.65
DN8/10	50	275	90	16	19.05	1.65

135 Series Main Dimension
(Tri-clamp connection)

Size	Actuator (mm)	K	L	ASME BPE			
				D	B	d	H
DN1.5/3/6	50	275	122	25	12.7	9.4	20
DN8/10	50	275	122	25	19.05	15.75	20

Single Acting, Normally Closed (NC)-Enter Below Seat Pressure Selection Table

Size	Orifice (mm)	Flow value Kv(m³/h)	Actuator (mm)	Differential pressure range ΔP(MPa)	Control pressure (MPa)
BPE-DN1.5	1.5	0.09	50A	0–1.0	≥0.45
BPE-DN3	3	0.26	50A	0–1.0	≥0.45
BPE-DN6	6	0.8	50A	0–1.0	≥0.45
BPE-DN8	8	1.43	50A	0–1.0	≥0.45
BPE-DN10	10	2.16	50A	0–1.0	≥0.45

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Opening (%) - Kv value (m³/h) chart of proportional angle seat valve

Size	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
BPE-DN1.5	0.011	0.021	0.032	0.043	0.054	0.064	0.073	0.082	0.085	0.09
BPE-DN3	0.025	0.059	0.1	0.13	0.16	0.19	0.21	0.23	0.24	0.26
BPE-DN6	0.03	0.075	0.156	0.247	0.332	0.442	0.53	0.63	0.726	0.8
BPE-DN8	0.05	0.15	0.26	0.39	0.53	0.73	0.98	1.27	1.42	1.43
BPE-DN10	0.1	0.26	0.42	0.61	0.82	1.08	1.45	1.8	2.03	2.16

Multi-channel Valve

103 Series
Threaded Pneumatic
Three-way Angle
Seat Valve




103 Series
Tri-clamp Pneumatic
Three-way Angle
Seat Valve



Technical Specification



- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8M/CF3M and other special materials
- Actuator material: CF8
- Seal material: PTFE
- Fluid temperature: –10°C — +180°C
- Ambient temperature: –10°C — +80°C
- Control type: Single acting normally closed,
Double acting normally closed,
Double acting without spring
- Connection type: Threaded connection, Tri-clamp
- Applicable medium: Water, Steam, Oil, Neutral gas or Liquid,
Organic solvent, Acid and lye
- Leakage class: DIN EN 12266 Class A

Order Instruction



Function Principle

When the valve is in idle state, C port is closed due to spring force.
When the actuator piston is compressed, C port is opened and B
port is closed. When double acting, the valve opens and closes by









Main Dimension (Threaded connection)

Size	Actuator	Q	C	R	G	A	K	L	SW	Weight (kg)
DN15	40	1/8"	50.5	27	1/2"	195	50	68	27	0.91
DN20	50	1/8"	60	33	3/4"	230	60	75	32	1.25
DN25	50	1/8"	60	33	1"	242	68	90	40	1.64
DN32	63	1/8"	75	41	1 1/4"	301	86	116	50	3.26
	90	1/8"	106	55	1 1/4"	355	86	116	50	4.62
DN40	63	1/8"	75	41	1 1/2"	306	90	116	56	3.79
	90	1/8"	106	55	1 1/2"	360	90	116	56	5.15
DN50	90	1/8"	106	55	2"	382	102	138	69	6.52

Main Dimension (Tri-clamp connection)

Size	Actuator	Q	C	R	ΦD	Φd	Φd1	A	K	L	Weight (kg)
DN15	40	1/8"	50.5	27	34	16	16	223	80	90	0.99
DN20	50	1/8"	60	33	50.5	19	19	246	80	90	1.48
DN25	50	1/8"	60	33	50.5	26	26	262	90	100	1.78
DN32	63	1/8"	75	41	50.5	31	29	319	104	130	3.39
	90	1/8"	106	55	50.5	31	29	373	104	130	4.75
DN40	63	1/8"	75	41	64	35	33	327	111	150	4.09
	90	1/8"	106	55	64	35	33	381	111	150	5.45
DN50	90	1/8"	106	55	64	43	43	408	128	160	6.65



Multi-channel Valve

Single Acting, Normally Closed

Size	Actuator	Interface	Orifice	Flow value Kv(m³/h)		Split function		Blend function		Reversal function	
				A-B	A-C	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)
DN15-A	40	1/2"	14	4.1	4.9	0-1.6	0.4-0.6	0-1.2	0.4-0.6	0-1.4	0.4-0.6
DN20-A	50	3/4"	18	5.8	6.5	0-1.6	0.45-0.65	0-1.4	0.45-0.65	0-1.6	0.45-0.7
DN20-B						0-1.6	0.3-0.55	0-0.8	0.3-0.55	0-1.6	0.3-0.7
DN25-A	50	1"	24	13.9	14.4	0-1.1	0.45-0.65	0-0.6	0.45-0.65	0-0.7	0.45-0.7
DN25-B						0-1.4	0.3-0.65	0-0.3	0.3-0.65	0-1.2	0.3-0.7
DN32-A	90	1 1/4"	31	20.9	22.8	0-0.55	0.6-0.7	0-1.6	0.6-0.7	0-1.0	0.6-0.7
DN32-B						0-1.4	0.45-0.7	0-1.2	0.45-0.7	0-1.6	0.45-0.7
DN32-C						0-1.6	0.3-0.45	0-0.2	0.3-0.45	0-1.6	0.3-0.5
DN40-A	90	1 1/2"	35	24.4	26.6	0-0.45	0.6-0.7	0-1.6	0.6-0.7	0-0.6	0.6-0.7
DN40-B						0-1.2	0.45-0.7	0-1.0	0.45-0.7	0-1.6	0.45-0.7
DN40-C						0-1.6	0.3-0.5	0-0.1	0.3-0.5	0-1.6	0.3-0.6
DN50-A	90	2"	45	29.3	31.9	0-0.25	0.6-0.7	0-0.9	0.6-0.7	0-0.3	0.6-0.7
DN50-B						0-0.9	0.45-0.7	0-0.5	0.45-0.7	0-0.8	0.45-0.7
DN50-C						0-1.6	0.3-0.6	—	—	0-1.6	0.3-0.7

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Double Acting, Normally Closed

Size	Actuator	Interface	Orifice	Flow value Kv(m³/h)		Split function		Blend function		Reversal function	
				A-B	A-C	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)
DN15-A	40	1/2"	14	4.1	4.9	0-1.6	0.4-0.6	0-1.6	0.4-0.6	0-1.4	0.4-0.6
DN20-B	50	3/4"	18	5.8	6.5	0-1.6	0.3-0.55	0-1.6	0.3-0.55	0-1.6	0.3-0.7
DN25-B	50	1"	24	13.9	14.4	0-1.4	0.3-0.65	0-1.4	0.3-0.65	0-1.2	0.3-0.7
DN32-D	63	1 1/4"	31	20.9	22.8	0-1.3	0.35-0.7	0-1.3	0.35-0.7	0-1.3	0.35-0.7
DN32-C	90	1 1/4"	31	20.9	22.8	0-1.6	0.3-0.55	0-1.6	0.3-0.55	0-1.6	0.3-0.55
DN40-D	63	1 1/2"	35	24.4	26.6	0-1.0	0.35-0.7	0-1.0	0.35-0.7	0-1.0	0.35-0.7
DN40-C	90	1 1/2"	35	24.4	26.6	0-1.6	0.3-0.6	0-1.6	0.3-0.6	0-1.6	0.3-0.6
DN50-C	90	2"	45	29.3	31.9	0-1.6	0.3-0.65	0-1.6	0.3-0.65	0-1.6	0.3-0.7

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Double Acting Without Spring

Size	Actuator	Interface	Orifice	Flow value Kv(m³/h)		Split function		Blend function		Reversal function	
				A-B	A-C	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)
DN15	40	1/2"	14	4.1	4.9	0-1.6	0.3-0.5	0-1.6	0.3-0.5	0-1.6	0.3-0.5
DN20	50	3/4"	18	5.8	6.5	0-1.6	0.3-0.5	0-1.6	0.3-0.5	0-1.6	0.3-0.5
DN25	50	1"	24	13.9	14.4	0-1.6	0.3-0.55	0-1.6	0.3-0.6	0-1.6	0.3-0.55
DN32	63	1 1/4"	31	20.9	22.8	0-1.6	0.3-0.6	0-1.6	0.3-0.6	0-1.6	0.3-0.6
	90	1 1/4"	31	20.9	22.8	0-1.6	0.3-0.4	0-1.6	0.3-0.45	0-1.6	0.3-0.4
DN40	63	1 1/2"	35	24.4	26.6	0-1.5	0.3-0.7	0-1.4	0.3-0.65	0-1.5	0.3-0.7
	90	1 1/2"	35	24.4	26.6	0-1.6	0.3-0.45	0-1.6	0.3-0.5	0-1.6	0.3-0.45
DN50	90	2"	45	29.3	31.9	0-1.6	0.3-0.6	0-1.6	0.3-0.6	0-1.6	0.3-0.6

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

103 Series
Low-Flow-Resistance
3-Way Angle Seat Valve



Technical Specification

- Operating pressure: 0-16bar (0-232psi)
- Control pressure: 3-8bar (43.5-116psi)
- Control medium: Filtered compressed air or neutral gas
- Body material: CF8M/CF3M and other special materials
- Actuator material: CF8
- Seal material: PTFE
- Medium temperature: -10°C — +180°C
- Ambient temperature: -10°C — +80°C
- Control type: Single acting normally closed,
Double acting normally closed,
Double acting without spring
- Connection type: Tri-clamp
- Applicable medium: Water, Steam, Oil, Neutral gas or Liquid,
Organic solvent, Acid and lye
- Leakage class: DIN EN 12266 Class A

Function Principle


We can achieve flow reversing, diverting and mixing functions with this valve. To a certain extent, this 3-way angle seat valve can replace two 2-way valves. At non-operating state, port C is closed, while port A and port B are interlinked. When give control air to actuator, port C and port A is interlinked, but channel between port A and port B is closed. If choose double acting control type, air control to open

Advantages

- Low-residue design, easy to clean.
- Large flux, low resistance; flow resistance can be reduced by 50%, flow rate can be increased by 40%.
- Stainless steel actuator suitable for harsh working conditions and



Multi-channel Valve



Main Dimension (Tri-clamp connection)

Size	Actuator	Q	C	R	D	d	A	K	H	L	Weight (kg)
DN20	50	1/8"	50.5	27	50.5	22.5	200	140	76	165	1.98

Single Acting Control

Size	Actuator	Orifice	Flow value Kv(m³/h)			A→B&A→C		B→A&C→A		B→A&A→C	
			A-B	B-A	A-C	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)
DN20-A	50	24	9.5	11.9	9.8	0-1.0	0.5-0.7	0-0.6	0.5-0.65	0-1.0	0.5-0.7
DN20-B						0-1.6	0.35-0.7	0-0.3	0.35-0.45	0-1.6	0.35-0.7

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Double Acting Normally Closed Control

Size	Actuator	Orifice	Flow value Kv(m³/h)			A→B&A→C		B→A&C→A		B→A&A→C	
			A-B	B-A	A-C	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)
DN20-B	50	24	9.5	11.9	9.8	0-1.6	0.35-0.7	0-1.6	0.35-0.7	0-1.6	0.35-0.7

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Double Acting Without Spring Control

Size	Actuator	Orifice	Flow value Kv(m³/h)			A→B&A→C		B→A&C→A		B→A&A→C	
			A-B	B-A	A-C	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)	Differential pressure range(MPa)	Control pressure (Mpa)
DN20	50	24	9.5	11.9	9.8	0-1.6	0.3-0.6	0-1.6	0.3-0.7	0-1.6	0.3-0.6

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

109 Series
Pneumatic
Modular Valve



Technical Specification


- Operating pressure: 0-16bar (0-232psi)
- Control pressure: 3-8bar (43.5-116psi)
- Control medium: Filtered compressed air or neutral gas
- Body material: CF8M/CF3M and other special materials
- Actuator material: CF8
- Seal material: PTFE
- Medium temperature: -10℃ — +180℃
- Ambient temperature: -10℃ — +80℃
- Control type: Single acting normally closed, Double acting normally closed, Double acting without spring
- Connection type: Tri-clamp
- Applicable medium: Water, Steam, Oil, Neutral gas or Liquid, Organic solvent, Acid and lye
- Leakage class: DIN EN 12266 Class A

Function Principle


When the valve is in idle state, due to the spring force the valve is Normally Closed (No.3 port), the bottom two ports are Normally Open (No.2 port); When the actuator piston is pressed by air, the valve opens, fluids from NO.3 port goes into No.1 and No.2 ports. When Double

Advantages

- Easy to clean
 - Seat is separate from the public ports. Well machined inner wall of the public ports ensures a smooth flow.
 - The valve utilizes bottom seal and seal ring for connection to valve stem in order to avoid fluid residue and allow effortless cleaning.
- The modular valve system is easy to install and assemble, allowing many different layouts. It is a good choice for mixing, distributing




Multi-channel Valve



Main Dimension

Size	Actuator	Q	ØD	Ød	Ød1	Ød2	H	H1	L1	L2	L3	L
DN10	40	1/8"	34	19	12	15	134	20	45	45	43	90
DN20	50	1/8"	50.5	29.5	24	24	140	30	60	60	43	120
DN25	63	1/8"	50.5	34	29.5	29.5	165	39	65	63.5	55	130

Order Instruction



110 Series
Pneumatic
Manifold Valve



Technical Specification


- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control medium: Filtered compressed air or neutral gas
- Seal material: PTFE
- Body material: CF8/CF8M/CF3M and other special materials
- Applicable medium: Water, Oil, Ail and other liquid
- Medium temperature: –10°C — +180°C, +25°C — +220°C
- Ambient temperature: –10°C — +80°C
- Connection type: Welded, Threaded, Tri-clamp, Diamond flange
- Control type: Single acting normally closed,
Double acting normally closed,
Double acting without spring

Advantages


Manifold valve adopts three-way connection design for optimal pipeline layout. It has aesthetic appearance, compact structure,



Order Instruction




Multi-channel Valve



Main Dimension (Threaded connection)

Size	A	K	L	ΦD	Φd	G	SW	ΦE	2-ΦF	Flow value Kv(m³/h)	Weight (kg)
DN15	153	35	76	25	18	1/2"	27	50	8.5	8.1	1.2
DN25	153	46	90	32	24	1"	39	57	8.5	14.8	1.35




Main Dimension (Welded connection)

Size	A	K	L	ΦD	Φd	Φd1	Φd2	ΦE	2-ΦF	Flow value Kv(m³/h)	Weight (kg)
DN20	153	30	76	25	18	21	25	50	8.5	8.1	1.2
DN25	153	36	90	32	24	27	32	57	8.5	14.8	1.3


Main Dimension (Tri-clamp connection)

Size	A	K	L	ΦD	Φd	ΦE	2-ΦF	Flow value Kv(m³/h)	Weight (kg)
DN20	153	50.5	76	25	21	50	8.5	8.1	1.3
DN25	153	57	90	32	27	57	8.5	14.8	1.4



Main Dimension (Diamond flange connection)

Size	A	K	L	ΦD	Φd	Φd1	d2	E	2-ΦF	Flow value Kv(m³/h)	Weight (kg)
DN20	153	36.5	76	25	18	31.3	50	50	8.5	8.1	1.2
DN25	153	43	90	32	24	40	57	57	8.5	14.8	1.4



Name	Size	D	d	H	L	E	F	Remark
Flange cover 1	DN15/DN20	/	/	/	8	50	8.5	Blind hole concave cover
	DN25	/	/	/	8.5	57	8.5	Blind hole concave cover
Flange cover 3	DN15/DN20	25.1/25.6	20	1.5	8	50	8.5	Through hole concave cover
	DN25	32.5	28	1.5	8.5	57	8.5	Through hole concave cover

Name	Size	D	d	H	L	E	F	Remark
Flange cover 2	DN15/DN20	/	/	/	6	50	8.5	Blind hole convex cover
	DN25	/	/	/	6	57	8.5	Blind hole convex cover
Flange cover 4	DN15/DN20	25.6	20	3	6	50	8.5	Through hole convex cover
	DN25	32.5	29	1.5	6	57	8.5	Through hole convex cover

Pressure Data Sheet

	Size	Actuator	Single acting valve operating pressure (MPa)			Double acting valve operating pressure (MPa)		
			Enter above seat ΔP (Mpa)	Enter below seat ΔP (Mpa)	Control pressure (Mpa)	Enter above seat ΔP (Mpa)	Enter below seat ΔP (Mpa)	Control pressure (Mpa)
Config. A	DN15	50	0-1.6	0-0.7	0.3-0.5	0-1.6	0-1.6	0.3-0.5
	DN20	50	0-1.6	0-0.7	0.3-0.5	0-1.6	0-1.6	0.3-0.5
	DN25	50	0-1.6	0-0.4	0.3-0.65	0-1.6	0-1.6	0.3-0.65
Config. B	DN15	50	0-1.6	0-1.4	0.45-0.6	0-1.6	0-1.6	0.45-0.6
	DN20	50	0-1.6	0-1.4	0.45-0.6	0-1.6	0-1.6	0.45-0.6
	DN25	50	0-1.4	0-0.8	0.45-0.7	0-1.4	0-1.6	0.45-0.7

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Filling Valve

1AA Series
27mm Actuator
Pipe-less Filling Valve




1AB Series
Pipe-less Filling Valve



Technical Specification


- Control type: Double acting normally closed, Double acting without spring
- Operating pressure: 0–7bar (0–102psi)
- Control medium: Filtered compressed air or neutral gas
- Control pressure: 3–4.5bar (44–65psi)
- Body material: CF8/CF8M/CF3M and other special materials
- Seal material: PTFE
- Medium temperature: –10°C — +120°C
- Ambient temperature: –10°C — +80°C
- Connection type: Threaded connection (BSP, BSPT, NPT)



1AA Series 27mm Actuator
Pipe-less Filling Valve

Advantages

- The filling valves is widely used in filling machinery, suitable for viscous, pasty and even foamy fluids with accurate and stable filling.
- 1AA series with 27mm actuator and 1AS series, the valve core made a flexible seat, it can be the self-adjustable



1AB Series
Pipe-less Filling Valve

1AC/1AF Series
Filling Valve with
Internal Sealing



1AP Series
Filling Valve with Internal
Sealing and Suction




Technical Specification


- Control type: Double acting normally closed, Double acting without spring
- Operating pressure: 0–7bar (0–102psi)
- Control pressure: 3–4.5bar (44–65psi)
- Body material: CF8M/CF3M and other special materials
- Seal material: PTFE
- Medium temperature: –10°C — +120°C
- Ambient temperature: –10°C — +80°C

Advantages

- It is widely used in filling machinery, especially for applications with viscous, pasty and even foamy fluids.
- Fast, accurate and stable filling.
- Delicate and compact, easy to arrange pipeline layout.
- Special nozzle structure and sealing design ensure no dripping leakage.
- Bottom chamfer structure of the filling nozzle self-locates and enables submerged filling.



1AC Filling Valve with Internal Sealing 1AF Filling Valve with Internal Sealing



1AP Filling Valve with Internal Sealing and Suction

1AC/1AF Main Dimension

Size	ΦD	Φd	H	H1
1AC	20	10	267	130
1AC	18	9	267	130
1AF	16	8	267	130



Filling Valve

1AL/1AM Series
Filling Valve with
Internal Sealing



1AL/1AM Series
Filling Valve with Internal
Sealing and Suction



1AD Series
Filling Valve with
External Sealing




* Accessory can be installed on top of actuator

Technical Specification

- Control type: Double acting normally closed, Double acting without spring
- Operating pressure: 0–7bar (0–102psi)
- Control pressure: 3–4.5bar (44–65psi)
- Body material: CF8M
- Seal material: PTFE
- Medium temperature: –10°C — +120°C
- Ambient temperature: –10°C — +80°C

Advantages

1. It is widely used in filling machinery, especially for applications with viscous, pasty and even foamy fluids.
2. Fast, accurate and stable filling.
3. Delicate and compact, easy to arrange pipeline layout.
4. Special nozzle structure and sealing design ensure no dripping leakage.
5. Bottom chamfer structure of the filling nozzle self-locates and enables submerged filling.
6. The head gourd shape design of the filling tube reduces weight and cost without sacrificing flow rate.
7. With super strong suction function, it can timely recover the



1AJ/1AE/1AK Series
Filling Valve with External
Sealing and Suction



1AG/1AI/1AH Series
Filling Valve with External
Sealing and Suction




Technical Specification

- Control type: Double acting normally closed, Double acting without spring
- Operating pressure: 0–7bar (0–102psi)
- Control pressure: 3–4.5bar (44–65psi)
- Body material: CF8M/CF3M and other special materials
- Seal material: PTFE
- Medium temperature: –10°C — +120°C
- Ambient temperature: –10°C — +80°C

Advantages

1. Superior performance in easy foaming fluids filling.
2. Delicate and compact structure easy for pipeline layout.
3. Fast and stable filling.
4. Special suction design ensure no dripping leakage.
5. Special tip seal structure enables convenient maintenance and



1AJ/1AG/1AE/1AI/1AK/1AH Series

Main Dimension

Size	Φ D	Φ d	H1	H
1AJ	20	17	300	502
1AG	20	17	130	332
1AE	16	13	300	502
1AI	16	13	130	332
1AK	12	9	300	502
1AH	12	9	130	332

Filling Valve

1A1 Series Sauce Filling Valve with Internal Sealing




Technical Specification


- Control type: Double acting without spring
- Operating pressure: 0–7bar (0–102psi)
- Control pressure: 4–7bar (58–102psi)
- Control medium: CF8M/CF3M and other special materials
- Seal material: UPE
- Medium temperature: –10°C — +110°C
- Ambient temperature: –10°C — +60°C

Advantages

1. Widely used in filling machinery. Suitable for viscous, granular sauce filling. Such as beef sauce, chili sauce, bean paste, etc.
2. Fast, accurate and stable filling.
3. The internal structure adopts plunger design, resulting in easy cleaning and minimal residue.
4. The filling body and the connection are connected by tri-clamp, so that they can be installed, uninstalled, and adjusted easily.
5. Long valve stroke enables large-capacity filling.
6. Accessories, such as proximity switch and position indicator, can be installed on top of actuator to enable feedback of valve open



DN20 outline drawing



DN25 outline drawing

1A2 Series Filling Valve with Internal Sealing



* Customization available


Technical Specification

- Control type: Double acting normally closed,
Double acting without spring
- Operating pressure: 0–7bar (0–102psi)
- Control pressure: 3–4.5bar (44–65psi)
- Body material: CF8M/CF3M and other special materials
- Seal material: PTFE
- Medium temperature: –10°C — +120°C
- Ambient temperature: –10°C — +80°C

Advantages

1. It is widely used in filling machinery, especially for applications with viscous, pasty and even foamy fluids.
2. Fast, accurate and stable filling.
3. Delicate and compact, easy to arrange pipeline layout.
4. Special nozzle structure and sealing design ensure no dripping leakage.
5. Bottom chamfer structure of the filling nozzle self-locates and enables submerged filling.
6. The valve utilizes bottom seal and seal ring for connection to valve stem in order to avoid fluid residue and allow effortless cleaning.
7. Internal suction structure recovers dripping liquid along the pipe

Filling Valve



Main Dimension (1A2 Series)

Size	Connection method	Actuator	ΦD	Φd	F	H	H1	Φ E (Optional)
DN15	Threaded connection Tri-clamp connection	32	12	5	G1/2 NPT1/2 BSPT1/2 Φ 16	220-540	60-380	Φ 20/M22X1.5
			14	6.5				Φ 25/M25X1.5
			16	8				
			18	9				
			20	10				
24	13							
DN20	Threaded connection	32	18	9	G3/4" NPT3/4" BSPT3/4" M26X1.5	227-547	60-380	Φ 28/M28X1.5
			20	10				Φ 30/M30X1.5
			22	11.5				
			24	13				
			26	14				
			28	16				
DN25	Tri-clamp connection	32	18	9	Φ 22	227-547	60-380	Φ 28/M28X1.5
			20	10				Φ 30/M30X1.5
			22	11.5				
			24	13				
			26	14				
			28	16				

Order Instruction

1AX	XXX	X	XXX	XX	XXX	X	X	XX		X	X	(*)
Series	Actuator	Control type	Inlet size	Pipe outer diameter (mm)	Pipe length (mm)	Sealing structure	Suction	Connection type	Valve securement	Body Material	Special customization EC 1935	
		2:Double acting normally closed				I: Internal sealing	0: Without suction	G1: Threaded BSP DIN ISO 228-1	O: No securement	1: CF8		
		3:Double acting without spring				E: External sealing	1: With suction	T1: Threaded BSPT DIN 2999-1/ISO7-1	M: Thread securement D: Pipe securement	2: CF8M 6: CF3M		
								N1: Threaded NPT ASMEB1.20.1				
								M1: M26*1.5				
								H7: WeldedDIN11850-2/DIN11866 A				
								H8: WeldedDIN11850-3				
								H9: Welded Chamfer				
								K7: Tri-clamp ISO2852-50.5				
1AA	A27	2/3	D10	00	000	I	0	G1/T1/N1	0	1/2/6		
	A27	2/3	D15	00	000	I	0	G1/T1/N1/H7/H8/H9/K7	0	1/2/6		
1AB	A27	2/3	D15	00	000	I	0	G1/T1/N1	0	1/2/6		
1AC	A27	2/3	D15	20	130	I	0	G1/T1/N1	M/D	2/6		
	A27	2/3	D15	18	130	I	0	G1/T1/N1	M/D	2/6		
1AF	A27	2/3	D15	16	130	I	0	G1/T1/N1	M/D	2/6		
1AP	A32	2/3	D15	20	130	I	1	G1/T1/N1/K7	M/D	2/6		
1AD	A27	2/3	D15	14	175	E	0	G1/T1/N1	M/D	2/6		
1AJ	A32	2/3	D15	20	300	E	1	G1/T1/N1/k7	M/D	2/6		
1AG	A32	2/3	D15	20	130	E	1	G1/T1/N1/k7	M/D	2/6		
1AE	A32	2/3	D15	16	300	E	1	G1/T1/N1/k7	M/D	2/6		
1AI	A32	2/3	D15	16	130	E	1	G1/T1/N1/k7	M/D	2/6		
1AK	A32	2/3	D15	12	300	E	1	G1/T1/N1/k7	M/D	2/6		
1AH	A32	2/3	D15	12	130	E	1	G1/T1/N1/k7	D	2/6		
1AL	A40	2/3	D25	42	150	I	0/1	K7	D	2/6		
1AM	A40	2/3	D25	50	150	I	0/1	K7	D	2/6		
	A32	3	D25	29	40	/	0	K7	/	1/2/6		
1A1	A32	3	D32	34	40	/	0	K7	/	1/2/6		
1A2	A32	2/3	D15	12	60-380	I	0	G1/T1/N1/K7	M/D	2/6		
			14									
			16									
			18									
			20									
			24									
		D20	18	G1/T1/N1/M1								
			20									
			22									
			24									
			26									
			28									
		D25	18	K7								
			20									
			22									
			24									
			26									
			28									



Shuttle Valve

200 Series
Pneumatic
Shuttle Valve



200 Series
Tri-clamp Pneumatic
Shuttle Valve



Technical Specification

- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control medium: Filtered compressed air or neutral gas
- Body material: CF8M/CF8
- Seal material: EPDM/FPM
- Applicable medium: FKM–Suitable for most fluid, except for steam.
EPDM–Suitable for steam and hot water, unsuitable for oils, greases, fuels etc.
- Medium temperature: –20°C — +150°C (FPM),
–20°C — +130°C (EPDM)
- Ambient temperature: –20°C — +80°C
- Control type: Single acting normally closed,
Single acting normally open,
Double acting normally closed,
Double acting without spring
- Connection type: Threaded connection (BSP、BSPT、NPT)
- Leakage class: DIN EN 12266 Class A

Function Principle


This valve opens and closes through piston motion forced by compressed air. As fluid pressure acts onto valve seat, the piston experiences little resistance and thereby enables the valve to quickly open/close. The latest design improvement results in more effluent

Advantages

- Compact and aesthetic design. Stainless steel body ensures superb durability.
- Easy to use with many possible mounting positions. Valve operates efficiently with minimum pressure loss.


Applications

- Food & Beverage
- Air Separation
- Filling Operation
- Ceramic Molding
- Semi-conductor Cleaning
- Automobile
- Others



Main Dimension (Threaded connection)

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50
Thread end	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
A (mm)	56	56	61	72	78	94	104	116
Ø D (mm)	46	46	52	64	69	86	96	108
SW (mm)	22	22	26.5	32	41	50	56	70
B (mm)	33	33	35	40	43	51	56	62
L (mm)	98	98	112	135	143	165	180	207
Weight (Kg)	0.78	0.76	1.06	1.54	1.92	3.15	3.92	6.0



Main Dimension (Tri-clamp connection)

Size	d	A	B	C	D	L
DN15	15	61	35	34	52	112.5
DN20	20	72	40	50.5	64	136
DN25	25	77.5	43	50.5	69	143.5
DN32	32	94	51	64	86	166
DN40	40	104	56	64	96	180.5
DN50	50	116	62	77.5	108	207

200 Series Pressure Data Sheet

Single Acting, Normally Closed-Above Seat

Size	Interface	Orifice mm	Flow value Kv(m³/h)	Differential pressure range MPa	Control Pressure Mpa
DN8	G1/4"	10	2.2	0-1.6	0.3-0.5
DN10	G3/8"	10	3.2	0-1.6	0.3-0.5
DN15	G1/2"	15	6.4	0-1.6	0.4-0.5
DN20	G3/4"	20	8.9	0-1.6	0.4-0.5
DN25	G1"	25	13.7	0-1.6	0.3-0.5
DN32	G1 1/4"	32	21.6	0-1.6	0.3-0.5
DN40	G1 1/2"	40	36.5	0-1.6	0.3-0.5
DN50	G2"	50	55.0	0-1.6	0.5-0.6

Single Acting, Normally Closed-Below Seat

Size	Interface	Orifice mm	Flow value Kv(m³/h)	Differential pressure range MPa	Control Pressure Mpa
DN8	G1/4"	10	2.2	0-1.6	0.3
DN10	G3/8"	10	3.2	0-1.6	0.3
DN15	G1/2"	15	6.4	0-1.6	0.4
DN20	G3/4"	20	8.9	0-1.6	0.4
DN25	G1"	25	13.7	0-1.0	0.3
DN32	G1 1/4"	32	21.6	0-1.4	0.3
DN40	G1 1/2"	40	36.5	0-1.2	0.3
DN50	G2"	50	55.0	0-0.8	0.5

Double Acting, Normally Closed-Above Seat

Size	Interface	Orifice mm	Flow value Kv(m³/h)	Differential pressure range MPa	Control Pressure Mpa
DN8	G1/4"	10	2.2	0-1.6	0.3-0.5
DN10	G3/8"	10	3.2	0-1.6	0.3-0.5
DN15	G1/2"	15	6.4	0-1.6	0.4-0.5
DN20	G3/4"	20	8.9	0-1.6	0.4-0.5
DN25	G1"	25	13.7	0-1.6	0.3-0.7
DN32	G1 1/4"	32	21.6	0-1.6	0.3-0.7
DN40	G1 1/2"	40	36.5	0-1.6	0.3-0.7
DN50	G2"	50	55.0	0-1.6	0.5-0.7

Double Acting, Normally Closed-Below Seat

Size	Interface	Orifice mm	Flow value Kv(m³/h)	Differential pressure range MPa	Control Pressure Mpa
DN8	G1/4"	10	2.2	0-1.6	0.3-0.5
DN10	G3/8"	10	3.2	0-1.6	0.3-0.5
DN15	G1/2"	15	6.4	0-1.6	0.4-0.5
DN20	G3/4"	20	8.9	0-1.6	0.4-0.5
DN25	G1"	25	13.7	0-1.6	0.3-0.7
DN32	G1 1/4"	32	21.6	0-1.6	0.3-0.7
DN40	G1 1/2"	40	36.5	0-1.6	0.3-0.7
DN50	G2"	50	55.0	0-1.6	0.5-0.7

Normally Open-Above Seat


Size	Interface	Orifice mm	Flow value Kv(m³/h)	Differential pressure range MPa	Control Pressure Mpa
DN8	G1/4"	10	2.2	0-1.6	0.5
DN10	G3/8"	10	3.2	0-1.6	0.5
DN15	G1/2"	15	6.4	0-1.6	0.5
DN20	G3/4"	20	8.9	0-1.6	0.5
DN25	G1"	25	13.7	0-1.6	0.5
DN32	G1 1/4"	32	21.6	0-1.6	0.5
DN40	G1 1/2"	40	36.5	0-1.6	0.5
DN50	G2"	50	55.0	0-1.6	0.6

Normally Open-Below Seat

Size	Interface	Orifice mm	Flow value Kv(m³/h)	Differential pressure range MPa	Control Pressure Mpa
DN8	G1/4"	10	2.2	0-1.6	0.5
DN10	G3/8"	10	3.2	0-1.6	0.5
DN15	G1/2"	15	6.4	0-1.6	0.5
DN20	G3/4"	20	8.9	0-1.6	0.5
DN25	G1"	25	13.7	0-1.6	0.7
DN32	G1 1/4"	32	21.6	0-1.6	0.7
DN40	G1 1/2"	40	36.5	0-1.6	0.7
DN50	G2"	50	55.0	0-1.6	0.7

Note: In order to ensure product performance, it is recommended to select product according to the highest value in the <= 90% pressure range

Open/Close



Closing

When hole "A" is supplied with air (hole "B" must be discharging), the piston moves towards and eventually presses onto the seat, thereby closing the valve.


For a single acting N.C. shuttle valve, a spring is installed in "A" chamber, pressing the piston against seat seal and allowing the

Opening

When hole "B" is supplied with air (hole "A" must be discharging), the piston move towards "C" and away from seat seal, thereby opening the valve.

For a single acting N.O. shuttle valve, a spring is installed in "B" chamber, forcing the piston away from seat seal and allowing the

Order Instruction




Shuttle Valve

Shuttle Valve
with Solenoid Valve



Solenoid Valve

Available accessories: 3/2 way and 5/2 way solenoid valve (NAMUR interface)



Technical Specification


- Connection type: G1/4"
- Air pressure: 3–8bar (43.5–116psi)
- Power: 220V AC 24V DC
- Voltage range: $\pm 10\%$
- Power consumption: AC 4.5W DC 3W
- Ambient temperature: -5°C — $+50^{\circ}\text{C}$
- Max frequency: 3 times/second
- Protection level: IP65
- Leakage class: DIN EN 12266 Class A

Shuttle Valve with
Magnetic Switch



Magnetic Switch

Magnetic switch mounted on 200 series shuttle valve can indicate the valve operating state and feedback open/close status signal.



Technical Specification


- Size: DN8–DN50
- Indication: Red LED
- Power: 10–30V DC
- Max.current: 100mA
- Cable: 2PVC cables
- Working temperature: -10°C — $+70^{\circ}\text{C}$
- Protection: IP67
- Leakage class: DIN EN 12266 Class A

Note: Since the magnets must be assembled inside the valve, the limit switches must be requested when ordering the valve.



Shuttle Valve

204 Series
Flanged Shuttle Valve




Technical Specification

- Operating pressure: Above seat 0–16bar (0–232psi)
Below seat 0–12bar (0–174psi)
- Control pressure: 3–5bar (43.5–72.5psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8
- Seal material: EPDM/(FKM can be customized)
- Applicable medium: EPDM–Suitable for steam and hot water,
unsuitable for oils, greases, fuels, etc.
FPM–Suitable for most fluid, except for steam.
- Fluid temperature: –20°C — +80°C (EPDM)
- Ambient temperature: –20°C — +80°C
- Control type: Double acting without spring
- Connection type: Flange
DIN2543/DIN2576/EN1092–1/HG20592
- Leakage class: DIN EN 12266 Class A


Main Dimension

Size	D	L	ΦE	ΦF	H	C	ΦM	ΦN	ΦP	α	Flow value Kv(m ³ /h)	Weight (kg)
DN65	85	192	145	4–Φ18	20	2	66	120	180	45°	139.3	10.0
DN80	92	212	160	8–Φ18	22	2	75	135	195	22.5°	202.6	13.32
DN100	102	227	180	8–Φ18	22	2	94	155	215	22.5°	288	16.30

Order Instruction



204 Series
Large-diameter
Shuttle Valve




Technical Specification

- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–5bar (43.5–72.5psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8
- Seal material: EPDM/(FKM can be customized)
- Applicable medium: EPDM–Suitable for steam and hot water,
unsuitable for oils, greases, fuels, etc.
FPM–Suitable for most fluid, except for steam.
- Fluid temperature: –20°C — +80°C (EPDM)
- Ambient temperature: –20°C — +80°C
- Control type: Double acting without spring
- Connection type: Flange
DIN2543/DIN2576/EN1092–1/HG20592
- Leakage class: DIN EN 12266 Class A


Main Dimension

Size	D	B	L	ΦE	ΦF	H	C	ΦM	ΦN	ΦP	α	Weight (kg)
DN125	256	114	295	210	8–Φ18	22	3	121	185	245	22.5°	36
DN150	281	127	356	240	8–Φ23	22	3	150	210	280	22.5°	45.8

Order Instruction



205 Series
Pneumatic High-pressure
Shuttle Valve




Technical Specification

- Operating pressure: 0–100bar (0–1450psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control medium: Filtered compressed air or neutral gas
- Flow Kv: 5(m³/h)
- Body material: CF8M/CF8
- Seal material: EPDM/FPM (customized)
- Applicable medium: EPDM—Suitable for steam and hot water, unsuitable for oils, greases, fuels, etc.
FPM—Suitable for most fluid, except for steam.
- Medium temperature: –20°C—+150°C (FPM), –20°C—+130°C (EPDM)
- Ambient temperature: –20°C—+80°C
- Control type: Single acting Normally closed, Double acting normally closed, Double acting without spring
- Connection type: Threaded connection (BSP, BSPT, NPT)
- Leakage class: DIN EN 12266 Class A

Advantages

- Small volume, beautiful appearance and long service life
Stainless steel body, high-graded appearance and corrosion resistant. The piston and the seal are combined into one, simple and reliable, with an ultra – long service life, and can be installed in any direction.
- High speed and low pressure loss.
Better medium flow state within the body. Since the medium pressure acts on the valve seat, the piston is hardly disturbed by resistance. Therefore, the switch speed is high and the pressure loss is low.
- High pressure resistant.
Excellent sealing performance, and applicable in high-pressure

Order Instruction



Pneumatic Butterfly Valve

300 Series
Pneumatic
Butterfly Valve




Technical Specification

- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–8bar (43.5–116psi)
- Applicable medium: EPDM—Suitable for steam and hot water, unsuitable for oils, greases, fuels, etc.
Medium temperature: –10°C—+130°C
- Body material: HT200
- Seal material: EPDM
- Disc material: CF8
- Control type: Double acting, Double acting without spring.


Function Principle

Compressed air rotates the blade, thereby opening and closing the valve. Unique valve design ensures low power loss, high efficiency,






Pneumatic Butterfly Valve



Main Dimension

Size	Operating pressure (Mpa)	Control Pressure (Mpa)	L (mm)	H (mm)	H1 (mm)	H2 (mm)	Φd (mm)	ΦD (mm)	Weight (kg)
DN50	0 - 1.6	0.3 - 0.8	38	372	110	75	52	102	4.7
DN65	0 - 1.6	0.3 - 0.8	38	380	117	76	66.5	110	4.8
DN80	0 - 1.6	0.3 - 0.8	42	395	120	89	76.5	128	5.3
DN100	0 - 1.6	0.3 - 0.8	48	442	144	110	100.5	160	7.7
DN125	0 - 1.6	0.3 - 0.8	48	468	156	124	125	185	8.1
DN150	0 - 1.6	0.5 - 0.8	52	468	156	124	152.5	218	10.8

Order Instruction



303 Series
Inclined Plate
Butterfly Valve



Technical Specification

- Product specification: DN50
- Operating pressure: 0-10bar
- Medium temperature: -10°C—+150°C
- Body material: CF8/CF8M/CF3M and other materials
- Seal material: FPM
- Connection type: Tri-clamp
- Application range: industrial grade/hygienic grade industries, media such as water/steam/powder

Advantages


- Patented inclined plate structural design. When the valve is opened, the butterfly plate is completely disengaged from the valve seat, resulting in little wear on the butterfly plate seal.
- Vulcanized sealing to prevent tearing and scraping.
- Progressive sealing structure and streamlined design of the valve body's sealing surface.
- The plate - rod is designed without a pin connection, making valve maintenance more convenient.
- The streamlined design of the valve body enables internal polishing

Main Dimension


Size	ΦD	L	Selection of double acting actuator	A Equipped with double acting actuator	Selection of single acting actuator	A Equipped with single acting actuator
DN50	Φ64	48	AT40	122	AT52	128

Pneumatic Butterfly Valve

303 Series
Inclined Plate
Butterfly Valve




Order Instruction



Manual Ball Valve

412 Series
1-PC Flanged Ball Valve
with Mounting Pad




Technical Specification

- Nominal pressure: PN40 (1/2"~2")
(Gas medium≤PN20);
PN16 (2-1/2 " ~ 4")
- Medium temperature: -10℃ — +120℃
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Applicable medium: Water、Oil、Gas
- Connection type: Flange DIN2501


Main Dimension

Size	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
d	15	20	25	32	38	50	64	76	96
D1	88	98	105	130	148	165	185	200	220
D2	65	75	85	100	110	125	145	160	180
D3	45	58	68	78	88	102	122	138	158
N-M	4-M12	4-M12	4-M12	4-M16	4-M16	4-M16	4-M16	8-M16	8-M16
L	37	40	44	52	64	83	107	120	145
W	140	140	165	165	195	195	260	260	300
H	80	85	93	104	115	125	145	152	180
S	9	9	11	11	14	14	17	17	17
ISO5211	F03/F04	F03/F04	F04/F05	F04/F05	F05/F07	F05/F07	F07/F10	F07/F10	F10
W1	36	36	42	42	50	50	70	70	\
W2	42	42	50	50	70	70	102	102	102
K1	6	6	6	6	7	7	9	9	\
K2	6	6	7	7	9	9	11	11	11
N·m	8	10	12	15	19	25	40	50	65

Order Instruction



Manual Ball Valve

421 Series
2-PC Ball Valve
(F/F)



Technical Specification

- Nominal pressure: PN63 (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Threaded connection (BSP, BSPT, NPT)

Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
ΦD	11	12	15	20	25	32	38	50	65	76	96
L	48.1	48.1	58	65.3	76.4	89	97	121	144.5	166	219
H	47.5	47.5	53.2	60	63.7	78.9	82.8	100	118	127	171
W	106.5	106.5	106.5	126.5	126.5	155.5	155.5	191.5	230	230	320

Order Instruction

422 Series
2-PC Ball Valve
(F/M)


Technical Specification

- Nominal pressure: PN63 (1/4"~2") (Gas medium ≤ PN20); PN55 (2~1/2"~4") (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Female thread (BSP, BSPT, NPT); Male thread (BSPT)


Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
ΦD	11.6	12.5	15	20	25	32	38	50	64	76	96
L	59	59.5	71	80.5	95	107.5	118.5	144	171.5	196	255
H	48	48	52.5	59	62.5	74	77.5	92.5	118	127	171
W	91.5	91.5	103	112.5	112.5	140	140	162	230	230	320

Order Instruction



Manual Ball Valve

431 Series
3-PC Threaded
Ball Valve



Technical Specification

- Nominal pressure: PN63 (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Threaded connection (BSP, BSPT, NPT)

Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
ΦD	12.5	12.5	15	20	25	32	38	50	64	76	100
L	50.5	50.5	61.5	70	80.5	93	103	125	162	175	216
H	48	48	52	61	65	79	83	97	121.5	132	175
W	100	100	100	127	127	154	154	192	230	230	320

Order Instruction

432 Series
3-PC Butt Weld
Ball Valve


Technical Specification

- Nominal pressure: PN63 (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Welded connection

Main Dimension


Size	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
ΦD	12.5	15	20	25	32	38	50	64	76	96
Φd	18	22	27.5	33.5	44	50	61.6	76.5	90	115
L	52.4	62.4	72.2	81.6	95	106	127.2	158	175	218
H	48	52	61	65	79	83	97	129.5	138.5	176
W	100	100	127	127	154	154	192	247	247	320

Order Instruction



Manual Ball Valve

433 Series
3-PC Flanged
Ball Valve




Technical Specification

- Nominal pressure: PN40 (Gas medium≤PN20)
- Medium temperature: -10℃ — +120℃
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Flange (DIN2545)


Main Dimension

Size	ΦD	D1	K	C	L	H	W	N/I
DN15	15	95	65	45	130	77	129	4-14
DN20	20	105	75	58	150	82	129	4-14
DN25	25	115	85	68	160	92	143	4-14
DN32	32	140	100	78	180	98	143	4-18
DN40	38	150	110	88	200	109	170	4-18
DN50	50	165	125	102	230	120	170	4-18
DN65	64	185	145	122	290	142	254	8-18
DN80	76	200	160	138	310	152	254	8-18
DN100	100	235	190	162	350	176	320	8-22

Order Instruction



434 Series
3-PC Extended Butt
Weld Ball Valve




Technical Specification

- Nominal pressure: PN63 (Gas medium≤PN20)
- Medium temperature: -10℃ — +120℃
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Extended butt weld

Main Dimension


Size	ΦD	Φd	Φd1	L	L1	H	W
DN15	15	18	15	93.5	25	52	100
DN20	20	22	19	100	25	61	127
		25.4	22.4				
		28	25				
		21	18				
DN25	25	25.4	22.4	107.5	25	65	127
		28	25				
		31.8	28.8				
		34	31				
DN32	32	31.8	28.8	118	25	79	154
		34	31				
		38.1	35.1				
		40	37				
DN40	38	38	35	127	25	83	154
DN50	50	40	37	127	18	97	192
		57	54				

Order Instruction



Manual Ball Valve

441 series
3-PC Butt Weld Ball Valve
with Mounting Pad



Technical Specification


- Nominal pressure: PN63 (Gas medium≤PN20)
- Medium temperature: -10℃ — +120℃
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Welded connection

Main Dimension


Size	DN10	DN15	DN20	DN25	DN32	DN40	DN50
ΦD	12.5	15	20	25	32	38	50
Φd	18	22	27.5	33.5	44	50	61.6
L	52.4	62.4	72.2	81.6	95	106	127.2
H	72	75	81	88	94	106	121
W	140	140	140	160	160	185	185
N · m	5	5	5	9.5	20.5	23	31

Note: Torques are reference values and may vary.

Order Instruction



442 Series
3-PC Extended Butt Weld Ball
Valve with Mounting Pad



Technical Specification


- Nominal pressure: PN63 (Gas medium≤PN20)
- Medium temperature: -10℃ — +120℃
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Extended butt weld

Main Dimension


Size	ΦD	Φd	Φd1	L	L1	H	W	N · m
DN15	15	18	15	93.5	25	75	140	5
DN20	20	22	19	100	25	81	140	5
		25.4	22.4					
		28	25					
DN25	25	21	18	107.5	25	88	160	9.5
		25.4	22.4					
		28	25					
DN32	32	31.8	28.8	118	25	94	160	20.5
		34	31					
		31.8	28.8					
		34	31					
DN40	38	38.1	35.1	127	25	106	185	23
		40	37					
DN50	50	38	35	127.5	18	121	185	31
		40	37					
DN50	50	57	54	127.5	18	121	185	31
		57	54					

Note: Torques are reference values and may vary.

Order Instruction



Manual Ball Valve

443 Series
3-PC Threaded Ball Valve
with Mounting Pad

Technical Specification



- Nominal pressure: PN63 (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Threaded connection (BSP, BSPT, NPT)

Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
ΦD	11.5	12.5	15	20	25	32	38	50	64	76	96
L	64	64	66	70.6	82	97	108.6	124.5	170	186	226
H	75	75	75	81	93	98	109	124	151	160	172
W	141	141	141	141	162	162	188	188	233	233	330
H1	42	42	42	48	55	60	70	85	105	114	128
h	9	9	9	9	11	11	15	15	18.5	18.5	18.5
E	9	9	9	9	11	11	14	14	17	17	17
ISO5211	F03	F03	F03	F03	F04	F04	F05	F05	F07	F07	F07
	F04	F04	F04	F04	F05	F05	F07	F07	F10	F10	F10
N·m	3	3	5	9	12	14	18	25	35	48	62

Note: Torques are reference values and may vary.

Order Instruction

445 Series
3-Way Ball Valve
with Mounting Pad

Technical Specification


- Nominal pressure: PN63 (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8/CF8M
- Ball material: CF8(304), CF8M(316)
- Seal material: PTFE
- Connection type: Threaded connection (BSP, BSPT, NPT);

Main Dimension


Size	d	L	H	W	h	L1	□J	ISO5211	L2	N·m
DN8	9.5	79	75	141	42	40	9	F03/F04	64	7
DN10	11.5	79	75	141	42	40	9	F03/F04	64	8
DN15	12.5	79	75	141	42	40	9	F03/F04	64	10
DN20	16	83	82	141	49.5	42	9	F03/F04	68	15
DN25	20	104	97	162	59	52.5	11	F04/F05	82	21
DN32	25	111	100	162	63	55.5	11	F04/F05	90	25
DN40	32	126	113	188	73.5	64.5	14	F05/F07	106	30
DN50	38	147	122	188	83	73.5	14	F05/F07	123	60

Note: Torques are reference values and may vary.

Order Instruction



Pneumatic Ball Valve

451 Series
Pneumatic
Ball Valve Type A


Technical Specification

- Nominal pressure: PN63 (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8, CF8M
- Ball material: CF8(304), CF8M(316)
- Seal ring and Packing: PTFE
- Control Pressure: 5bar
- Control type: Double acting
(Single-acting option is available upon request.)

Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50
G	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
ΦD	12.5	12.5	15	20	25	32	38	50
L	50.5	50.5	61.5	70	80.5	93	103	125
H	123	123	123	123	145	169	169	201
K	124	124	127	134	147	169	179	205
N · m	5	5	5	5	9.5	20.5	23	31

Note: Actuator selection is based on control pressure 5 bar; Torques are reference values, so selection may be different.

451 Series
Pneumatic
Ball Valve Type D

Technical Specification


- Nominal pressure: PN63(1000Psi) (Gas medium ≤ PN20)
- Medium temperature: -10°C — +120°C
- Body and bonnet material: CF8, CF8M
- Ball material: CF8(304), CF8M(316)
- Seal ring and Packing: PTFE
- Control Pressure: 5bar
- Control type: Double acting
(Single-acting option is available .)

Main Dimension


Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50
G	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
ΦD	12.5	12.5	15	20	25	32	38	50
L	50.5	50.5	61.5	70	80.5	93	103	125
H	110	110	110	110	157	169	169	192
K	107	107	109	117	150	172	182	208
N · m	5	5	5	5	9.5	20.5	23	31

Note: Actuator selection is based on control pressure 5 bar;
Torques are reference values, so selection may be different.

Order Instruction




Check Valve

502 Series
Swing Check Valve



Technical Specification

- Nominal pressure: PN16
- Medium temperature: -20°C — +180°C
- Connection type: Threaded connection (BSP, BSPT, NPT)
- Body material: CF8/CF8M
- Seal material: Metal-to-metal seal

Pressure-temperature Rating



Order Instruction

503 Series
2-PC Spring Vertical
Check Valve

Technical Specification

- Nominal pressure: DN8~DN65 PN63
DN80~DN100 PN55
- Medium temperature: -25°C — +180°C
- Connection type: Threaded connection (BSP, BSPT, NPT)
- Body material: CF8/CF8M
- Seal material: Metal-to-metal seal
- Minimum open pressure: 24~50mbar


Part List

No.	Part	Material	No.	Part	Material
1	Bonnet	CF8/CF8M	4	Body	CF8/CF8M
2	Gasket	PTFE	5	Spring	316
3	Disc	CF8/CF8M			


Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
M	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
ΦD	10	11	15	20	25	32	40	50	65	80	100
A	21	21	25	30.5	37	45.5	52.5	65	81.5	97	124
L	51.3	51.3	57	63.6	76.6	88.5	101.8	114.3	149.2	170.2	166.1

Order Instruction



Check Valve

508 Series
Wafer Type Disc
Check Valve

Technical Specification

- Nominal pressure: PN40
- Size: DN15–DN100
- Medium temperature: -20°C — $+300^{\circ}\text{C}$
- Connection type: Flange
- Body material: CF8/CF8M
- Seal material: Metal-to-metal seal
- Flange standards: DIN PN16, 25, 40
ANSI 150/300 Lbs
- Structure length: DIN3202 – K4
- Minimum open pressure: 35mbar



Part List

No.	Part	Material	No.	Part	Material
1	Body	CF8/CF8M	3	Spring	304/316
2	Bonnet	316	4	Disc	CF8/CF8M

Main Dimension

Size	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
ΦD	39	46	54	70	80	94	112	132	150
Φd	15	20	25	32	40	46	62	75	86
ΦC	34	40	50	62	70	85	100	120	140
L	16	19	22	28	32	40	46	50	60

Order Instruction

509 Series
Y-Spring Check Valve

Technical Specification

- Nominal pressure: PN16
- Size: DN8–DN50
- Medium temperature: -10°C — $+180^{\circ}\text{C}$
- Connection type: Threaded, Welded, Tri-clamp, Flanged
- Minimum open pressure: 30–40mbar


Function Principle

Medium enters valve body through inlet opening, pushes the valve stem and valve core upward, and thereby opens the valve. When the medium starts to flow back from the outlet, the spring force and pressure applied by the medium itself push the valve stem and





Part List

No.	Part	Material	No.	Part	Material
1	Bonnet	CF8/CF8M	6	Core	CF8/CF8M
2	Body seal	PTFE	7	Seat	PTFE
3	Body	CF8/CF8M	8	Core gasket	CF8/CF8M
4	Spring	304	9	Self-locking nut	304
5	Stem	304/316			

Order Instruction



Check Valve



Main Dimension (Threaded connection)

Size	DN08	DN10	DN15	DN20	DN25	DN32	DN40	DN50
L	68	68	68	75	90	116	116	138
H	43	43	43	48.5	57	72	77	89
ΦD	13	13	13	18	24	31	35	45
G	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"

Main Dimension (Welded connection)

Size	DN15	DN20	DN25	DN32	DN40	DN50
L	70	82	100	125	130	155
H	42	49	58	70	77	87
ΦD	13	18	24	31	35	45
Chamfer	ΦK*	22	29	35	39	45
	S*	3.5	5	5	4	4.5
DIN11850-2	ΦK	19	23	29	35	41
	S	1.5	1.5	1.5	1.5	1.5
DIN11850-3	ΦK	20	24	30	36	42
	S	2	2	2	2	2

Note: The marked dimensions are design dimensions of casting parts
(actual dimensions may vary and are for reference only)

Main Dimension (Tri-clamp connection)

Size	DN15	DN20	DN25	DN32	DN40	DN50
L	80	130	130	146	160	175
H	44	51	56	66	75	89
ΦD	13	18	24	31	35	45
ΦC*	20.5	25	33	37	40	53
ΦB	27.5	43.5	43.5	43.5	56.5	56.5
Φd*	15	19	27	31	34	45
ΦK	34	50.5	50.5	50.5	64	64

Note: The marked dimensions are design dimensions of casting parts
(actual dimensions may vary and are for reference only)

Main Dimension (Flanged connection)

Size	DN15	DN20	DN25	DN32	DN40	DN50
L	130	150	160	180	200	230
H	44	51	60	73	80	91
ΦD	13	18	24	31	35	45
C	2	2	2	2	3	3
K	14	14	14	16	16	16
ΦE	65	75	85	100	110	125
n-ΦF	4-14	4-14	4-14	4-18	4-18	4-18
ΦM	16	19	26	31	38	54
ΦN	45	56	65	78	84	100
ΦP	95	105	115	140	150	165
α	45°	45°	45°	45°	45°	45°


Strainer

601 Series
Single Cap Strainer



Technical Specification

- Nominal pressure: PN55(DN8–DN50)
PN16(DN65–DN80)
- Connection type: Threaded connection
(BSP、BSPT、NPT)
- Body material: CF8/CF8M
- Medium Temperature: -10°C — +180°C



Part List

No.	Part	Material
1	Body	CF8M/CF8
2	Filter	304
3	Gasket	PTFE
4	Cover	CF8M/CF8

Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80
ΦD	14	14	14	20	25	32	40	50	60	80
H1	37	37	37	45	54	59	66	77	93	118
L	65	65	65	80	90	105	120	138	178	210

Filter Option

Filter Option	DN8/ DN10/DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80
1 20 mesh perforated filter	√	√	√	√	√	√	√	√
2 30 mesh wired filter	√	√	√	√	√	√		
3 30 mesh + frame	√	√	√	√	√	√		
4 80 mesh + frame	√	√	√	√	√	√	√	
5 100 mesh + frame	√						√	√

Order Instruction


Series No.	601	XXX	X	XX	X	(*)	
		D08、D10、D15、 Series D20、D25、D32、 D40、D50、D65、D80					Body material 1: CF8 2: CF8M
Filter option: 1、2、3、4、5							Connection type G1: Threaded BSP DIN ISO 228-1 T1: Threaded BSPT DIN 2999-1/ISO7-1 N1: Threaded NPT ASME B1.20.1

Strainer

602 Series
Double Cap Strainer

Technical Specification

- Nominal pressure: PN55(DN8–DN50)
PN16(DN65–DN80)
- Connection type: Threaded connection
(BSP, BSPT, NPT)
- Body material: CF8/CF8M
- Medium Temperature: -10°C — +180°C



Part List

No.	Part	Material
1	Body	CF8M/CF8
2	Filter	304
3	Gasket	PTFE
4	Cover	CF8M/CF8
5	Bolt seal	PTFE
6	Threaded plug	CF8M/CF8


Main Dimension

Size	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80
ΦD	14	14	14	20	25	32	40	50	60	80
H2	44	44	44	52	63	67	74	86	104	128
L	65	65	65	80	90	105	120	138	178	210

Filter Option


Filter Option	DN8/ DN10/DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80
1 20 mesh perforated filter	✓	✓	✓	✓	✓	✓	✓	✓
2 30 mesh wired filter	✓	✓	✓	✓	✓	✓		
3 30 mesh + frame	✓	✓	✓	✓	✓	✓		
4 80 mesh + frame	✓	✓	✓	✓	✓	✓	✓	
6 100 mesh + frame	✓						✓	✓

Order Instruction

603 Series
Flanged Strainer

Technical Specification

- Nominal pressure: PN16
- Connection type: Flanged connection
- Body material: CF8/CF8M
- Medium Temperature: -10°C — +180°C
- Flange standards: JB/T82.1-1994;
ISO/DIN/JIS is also available




Main Dimension

Size	L	C	H	h	ΦE	n-ΦF	ΦM	ΦN	ΦP	α
DN15	145	2	14	37	65	4-14	16	45	95	45°
DN20	155	2	14	45	75	4-14	20	56	105	45°
DN25	155	2	14	54	85	4-14	25	65	115	45°
DN32	185	2	16	59	100	4-18	32	78	140	45°
DN40	200	3	16	66	110	4-18	36	84	150	45°
DN50	215	3	16	77	125	4-18	49	100	165	45°
DN65	290	3	18	93	145	4-18	66	120	185	45°
DN80	315	3	20	118	160	8-18	78	135	200	22.5°

Filter Option

Filter Option	DN8/ DN10/DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80
1 20 mesh perforated filter	✓	✓	✓	✓	✓	✓	✓	✓
2 30 mesh wired filter	✓	✓	✓	✓	✓	✓		
3 30 mesh + frame	✓	✓	✓	✓	✓	✓		
4 80 mesh + frame	✓	✓	✓	✓	✓	✓	✓	
5 100 mesh + frame	✓						✓	✓


Order Instruction





Pressure Reducing Valve

700 Series
Pressure Reducing Valve



* Product does not include pressure gauge, which can be ordered separately

Technical Specification

- Nominal pressure: PN25
- Pressure range: 1–6bar (15–87psi)、4–10bar (58–145psi)、8–13bar (116–189psi) , 3 options available
- Medium Temperature: –15℃ — +100℃
- Seal material: FPM
- Control type: Normally open
- Connection type: Threaded connection (BSP、BSPT、NPT)
- Body material: CF8M

Function Principle

Pressure reducing valve is a N.O. valve that controls incoming fluid pressure to a desired range at outlet, by adjusting spring force and balancing it with the pressure applied by the passing medium. It


Advantages

1. All valve parts are made of stainless steel CF8M, suitable for water, weak acid and weak base, etc.
2. The valve combines the structure design of a piston type valve and a diaphragm type valve to achieve superior service life.

Main Dimension


Size	G	H	L	Flow value Kv(m³/h)
DN15	1/2"	110	70	2.1
DN20	3/4"	110	85	3.4
DN25	1"	115	92	5.5

Order Instruction



Overflow Valve

701 Series
Overflow Valve



* Product does not include pressure gauge, which can be ordered separately

Technical Specification

- Nominal Pressure: PN25
- Pressure Range: 1–10bar (15–145psi)
- Medium Temperature: –15℃ — +100℃
- Seal Material: FPM
- Connection type: Threaded connection (BSP、BSPT、NPT)
- Body material: CF8M

Function Principle

Overflow valve is a N.C valve that limits fluid pressure under a desired threshold, by adjusting the spring force and balancing it with the pressure applied by medium at the inlet. It ensures


Advantages

1. All valve parts are made of stainless steel CF8M, suitable for water, weak acid and weak base, etc.
2. The valve combines the structure design of a piston type valve and a diaphragm type valve to achieve better service life.

Main Dimension

Size	G	H	L	Flow value Kv(m³/h)
DN15	1/2"	110	70	2.1
DN20	3/4"	110	85	3.4
DN25	1"	115	92	5.5


Order Instruction



ESG®

Thermodynamic Steam Trap

800 Series
Thermodynamic
Steam Trap



* Flange connection is available upon request

Technical Specification

- Operating Pressure: 0.5–42bar (7–609psi)
- Max. Operating Temp: 400°C


Advantages

1. Compact structure.
2. High durability due to stainless steel inner components and valve body.
3. Long service life.
4. Easy to service and repair.



Part List

No.	Part	Material
1	Body	ASTM CA40
2	Cover	CF8
3	Threaded plug	CF8
4	Disc	2Cr13
5	Filter	304 (30 mesh by default)

Order Instruction




Discharge Capacity



Main Dimension

Size	Thread end	Dimension (mm)					Weight (kg)
		L	H	H1	H2	AA	
DN15	1/2"	78	41	99.6	33	44	0.9
DN20	3/4"	90	49.2	109.2	39	48	1.2
DN25	1"	95	57.5	121.6	45	56	1.7

801 Series
Thermodynamic
Steam Trap





Technical Specification

- Operating Pressure: 0.3–10bar (4–145psi)
- Max. Operating Temp: 200°C

Advantages

1. Small and compact, highly efficient.
 2. Superb energy efficiency.
 3. Easy to install and operate, Significant energy saving, energy consumption reduced by 40%.
- Application: Drip legs, steam tracing, laundry equipment.

Discharge Capacity




Main Dimension

Size	Threa end	Dimension (mm)					Weight (kg)
		L	H	H1	H2	AA	
DN8	1/4"	40	23	31	16.5	18	0.07

Part List

No.	Part	Material
1	Cover	CF8
2	Disc	2Cr13
3	O-ring	Silicone rubber
4	Body	CF8


Thermodynamic Steam Trap

801 Series
Thermodynamic
Steam Trap


Advantages

1. Compact structure.
2. High durability due to stainless steel inner components and valve body.
3. Long service life.
4. Easy to service and repair.

Discharge Capacity



Order Instruction



Technical Specification


- Operating Pressure: 1–42bar (15–609psi)
- Max. Operating Temp: 400°C

Part List

No.	Part	Material
1	Cover	CF8
2	Disc	2Cr13
3	Body	ASTM CA40

Main Dimension

Size	G	H	L	AA	Weight (kg)
DN15	1/2"	56	70	40	0.5
DN20	3/4"	64	80	44	0.8
DN25	1"	75	89	55	1.25

802 Series
Ball Float Steam Trap


Technical Specification

- Nominal pressure: PN16
- Max allowable pressure PMA: 16bar (232psi)
- Max allowable temperature TMA : 250°C
- Max differential pressure: 8bar (116psi)
- Connection type: Threaded connection (BSP, BSPT, NPT)

Advantages

1. Application for both horizontal and vertical installation.
2. Stainless steel material with excellent corrosion resistance and durability.
3. Continuous discharge, with no impact from temperature, pressure and flow. Prevent water hammer due to steam condensation.
4. No steam leakage, minimal heat loss.
5. Automatically discharge non-condensing gas to avoid air resistance.
6. Large discharge capacity improves work efficiency.

Discharge Capacity




Main Dimension

Size	A	B	C	D
DN15	145	120	74	169
DN20	145	120	74	169
DN25	145	120	74	169

Part List

No.	Part	Material
1	Cover	CF8/CF8M
2	Body	CF8/CF8M
3	Stem	304
4	Gasket	Soft graphite
5	Internal component	Stainless steel







Thermodynamic Steam Trap

Special Note

Please keep valve in opposite direction of gravity.




Operating Condition




Ordering Instructions


- 1. The steam trap can be applied in three directions (as shown below), please indicate when ordering.
- 2. Both thread connection (BSP, BSPT, NPT) and socket welding



Order Instruction



803 Series
Thermostatic
Steam Trap




Technical Specification

- Nominal pressure: 2.5MPa
 - Connection: thread
 - Max working pressure PMO: 2.1MPa
 - Max working pressure difference ΔPMX: 2.1MPa
 - Max operating temperature TMO: 220°C
 - Four types of bellows:
 - A-Discharge condensate below saturation temperature of 3°C.
 - B-Discharge condensate below saturation temperature of 5°C.
 - C-Discharge condensate below saturation temperature of 15°C.
 - D-Discharge condensate below saturation temperature of 25°C.
- Attention: To avoid abnormal operation, accidents, or personal injury, please do not use this product beyond the specification range. If the technical standards or regulations of a country or region have special provisions for the above specifications, the product should be used in

Advantages

- The stainless steel thermostatic steam trap is widely applicable in various fields, including steam main pipes, heat tracing equipment dryers, and
1. Featuring a 'fault normally open' feature to ensure no condensate accumulation in the steam space;
 2. The structure is sturdy and lightweight, capable of withstanding superheated steam and water hammer;
 3. Automatic regulation of fixed undercooling throughout the entire pressure range;
 4. Excellent air emission performance;
 5. Can be installed horizontally or vertically;
 6. The filter screen with a large flow area and a compact structure has a large drainage capacity;

Output Chart



1. Pressure difference refers to the pressure difference between the inlet and outlet of the steam trap.
 2. Recommended safety factor not less than 2.
- Attention: Do not use the steam trap under conditions exceeding the maximum


Main Dimension

Size	L	W	H1	H2	Weight (kg)
DN15	75	53	33	17	0.59
DN20	75	53	33	17	0.54
DN25	78	53	33	21	0.63

Part List

No.	Part	Material
1	Body	CFS
2	gasket	copper
3	bolt	304
4	cover	CF8
5	diaphragm box	stainless steel
6	60 mesh filter	304
7	gasket	PTFE
8	seat	stainless steel


Order Instruction





Thermostatic Steam Trap

804 Series
Thermostatic
Steam Trap




Technical Specification

- Nominal pressure: 3.2MPa
- Connection: thread
- Max working pressure PMO: 2.1MPa
- Max working pressure difference ΔPMX: 2.1MPa
- Max operating temperature TMO: 220°C
- Four types of bellows:
 - A-Discharge condensate below saturation temperature of 3°C.
 - B-Discharge condensate below saturation temperature of 5°C.
 - C-Discharge condensate below saturation temperature of 15°C.
 - D-Discharge condensate below saturation temperature of 25°C.


Attention: To avoid abnormal operation, accidents, or personal injury, please do not use this product beyond the specification range.
If the technical standards or regulations of a country or region have special provisions for the above specifications, the product should be used in

Output Chart




1. Pressure difference refers to the pressure difference between the inlet and outlet of the steam trap.
 2. Recommended safety factor not less than 2.
- Attention: Do not use the steam trap under conditions exceeding the maximum

Order Instruction



805 Series
Thermostatic
Steam Trap




Technical Specification

- Nominal pressure: 1.0MPa
- Max allowable pressure PMA: 1.0MPa
- Max allowable temperature TMA: 200°C
- Max working pressure PMO: 0.6MPa
- Max operating temperature TMO: 165°C
- Four types of bellows:
 - A-Discharge condensate below saturation temperature of 3°C
 - B-Discharge condensate below saturation temperature of 5°C
 - C-Discharge condensate below saturation temperature of 15°C
 - D-Discharge condensate below saturation temperature of 25°C


Attention: To avoid abnormal operation, accidents, or personal injury, please do not use this product beyond the specification range.
If the technical standards or regulations of a country or region have special provisions for the above specifications, the product should be used in

Output Chart



1. Pressure difference refers to the pressure difference between the inlet and outlet of the steam trap.
 2. Recommended safety factor not less than 2.
- Attention: Do not use the steam trap under conditions exceeding the maximum

Order Instruction



Advantages

The stainless steel thermostatic steam trap is widely applicable in various fields, including steam main pipes, heat tracing equipment dryers, and

1. Free flow of cold water and seamless design in the true sense, maximum inhibition of bacterial aggregation.
2. The feature of 'fault normally open' minimizes the possibility of shutdown under critical operating conditions.
3. The valve nozzle design with a large opening can quickly discharge a large amount of air, ensuring fast start, preventing blockage, and ensuring continuous operation.
4. Tight structure, easy installation and maintenance.


Main Dimension

Size	H	d	D	L	H1	Weight (kg)
1/2"	51	9.4	25	88	16	0.47
3/4"	51	15.75	25	88	16	0.51
1"	66	22.6	50.5	88	16	0.65

Part List

No.	Part	Material
1	Top body	SS 316L
2	Low body	SS 316L
3	Sealing gasket	Silicon rubber VMQ
4	Clamp	SS 316L
5	Diaphragm	SS 316L

Thermostatic Steam Trap


806 Series
Thermostatic
Steam Trap

Technical Specification

- Nominal pressure: 1.0MPa
- Max allowable pressure PMA: 1.0MPa
- Max allowable temperature TMA: 220°C
- Max working pressure PMO: 0.8MPa
- Max working temperature TMO: 176°C
- Four types of bellows:
 - A- Discharge condensate below saturation temperature of 3°C
 - B- Discharge condensate below saturation temperature of 5°C
 - C- Discharge condensate below saturation temperature of 15°C
 - D- Discharge condensate below saturation temperature of 25°C

Attention: To avoid abnormal operation, accidents, or personal injury, please do not use this product beyond the specification range. If the technical standards or regulations of a country or region have special provisions for the above specifications, the product should be used in


Output Chart



1. Pressure difference refers to the pressure difference between the inlet and outlet of the steam trap.

Attention: Do not use the steam trap under conditions exceeding the maximum pressure difference, otherwise condensation water may

Order Instruction



Advantages

The all stainless steel thermal static steam trap is suitable for heat transfer in tracing pipelines with relatively small condensate flow rates and small heat

1. Free flow of cold water and seamless design in the true sense, maximum inhibition of bacterial aggregation.
2. The feature "Normally open on fault" minimizes the possibility of shutdown under critical operating conditions.
3. The valve nozzle design with a large opening can quickly discharge a large amount of air, ensuring fast start, preventing blockage, and ensuring continuous operation.
4. Tight structure, easy installation and maintenance.


Main Dimension

Size	H	W	D	Weight (kg)
1/2"	49	44	25	0.17
3/4"	49	44	25	0.19
1"	53	44	50.5	0.28

Part List

No.	Part	Material
1	Low body	SS 316L
2	Diaphragm	SS 316L
3	Top body	SS 316L


Other Valves

901 Series
Float Type
Air Eliminator

Technical Specification

- Nominal pressure: PN16
- Ball material: CF8M
- Seal material: FPM
- Control type: Automatic
- Medium temperature: -20°C —+ 200°C
- Applicable medium: Can be used for hot and cold water systems as well as other types of liquid medium

Differential pressure/flow rate chart




Function Principle

This valve operates automatically due to density difference between gas and liquid. When a mixture of gas and liquid enters from bottom of the valve, gas exits through the outlet at the top, while liquid pushes the float ball up and blocks the gas outlet. This valve could be easily dismantled for maintenance, usually without disturbing pipe


Main Dimension

Size	G	G1	ΦD	H	SW
DN15	1/2"	1/2"	122	134	47.5
DN20	3/4"	1/2"	122	134	47.5
DN25	1"	1/2"	122	134	47.5

Order Instruction



Other Valves

902 Series
Vacuum Breaker

Technical Specification

- Size: DN15
- Nominal pressure: PN25
- Valve material: 304
- Applicable medium: Mainly used for steam or liquid system


Attention

Valve must be installed in vertical position. The system connection port is located at the bottom of the valve. If used for steam system, it must be installed at the top of the system to prevent

Function Principle

Under normal condition, a steel ball inside the valve blocks connection to atmosphere due to gravity and pressure from pipeline. When vacuum occurs inside pipeline, the steel ball gets pushed out by atmospheric pressure, allowing air into


Operating Condition



■ The product must not be used under this condition.

- PMA Max.Allowable Pressure: 25bar, 120°C
- TMA Max.Allowable Temperature: 400°C, 13bar
- PMO Max.Operating Pressure for saturated steam service: 21bar
- TMO Max.Operating Temperature: 400°C, 13bar
- Min.Operating Temperature: 0°C


Order Instruction

908 Series
Threaded Drain Valve908 Series
Flanged Drain Valve


Technical Specification

- Size: DN50 (Threaded connection),
DN65、DN80 (Flange connection)
- Operating pressure: 0-8bar/0-5bar/0-5bar
- Control pressure: 3-8bar (43.5-116psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8
- Seal material: PTFE


- Applicable fluid: Water, Air, Paper pulp, etc.
- Actuator size: 63mm, 80mm
- Medium temperature: -10°C — +120°C
- Ambient temperature: -10°C — +80°C
- Control type: Double acting without spring



DN50



DN65




DN80

Other Valves


909 Series
Exhaust Valve

Technical Specification

- Size: DN50/DN80 (Threaded connection)
- Operating pressure: 0–8bar/0–5bar
- Control pressure: 3–8bar (43.5–116psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8
- Seal material: PTFE
- Applicable fluid: Gas
- Actuator size: 63mm/80mm
- Medium temperature: –10°C — +120°C
- Ambient temperature: –10°C — +80°C
- Control type: Double acting without spring



Order Instruction



Shut Off Valve

Z10 Series
Pneumatic Two-way Medium
Pressure Shut Off Valve

Technical Specification

- Operating pressure: 0–30bar (0–435bar)
- Control pressure: 3–4bar (43.5–58psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8/CF8M
- Seal material: PTFE
- Actuator material: CF8/AL
- Actuator size: 90mm/125mm(AL)
- Applicable fluid: Water, Nitrogen, Steam, etc
- Medium temperature: –10°C — +220°C
- Ambient temperature: –10°C — +80°C
- Control type: Single acting normally closed
- Connection type: Flange JIS 20K
(ASME CLASS300, DIN PN40, GB PN40 Customization available)


Advantages

1. Applicable to steam, compressed air, nitrogen, superheated water, etc.
2. High-quality PTFE sealing materials are adopted to ensure reliable sealing.
3. It can be widely used in rubber tire vulcanization, steam vulcanization



Shut Off Valve


Z10 Series
Pneumatic Two-way Medium
Pressure Shut Off Valve



Dimension

Size	Actuator (mm)	Q	A	K	L	C	H	E	n-F	M	N	P	α
DN15	90	1/8"	240	305	146	1	14	70	4-15	95	51	15	45°
DN20	90	1/8"	240	305	146	1	16	75	4-15	100	56	20	45°
DN25	90	1/8"	255	340	167	1	16	90	4-19	125	67	25	45°
DN40	125	1/4"	320	430	190	2	18	105	4-19	140	81	40	45°

Order Instruction



Z11 Series
Pneumatic Two-way Medium
Pressure Shut Off Valve



Technical Specification

- Operating pressure: 0-32bar (0-464bar)
- Operating temperature: -30°C — +220°C
- Control pressure: 2.5-3.5bar (36.25-50.75psi)
- Body material: CF8
- Channel type: Two-way, Three-way
- Seal material: PTFE
- Applicable fluid: High – temperature steam, Superheated water, Nitrogen
- Control type: Single acting normally closed, Single acting normally open
- Connection type: Flange JIS 20K (ASME CLASS300, DIN PN40, GB PN40 Customization available)

Product Application Industries and Features

- Applicable to steam, compressed air, nitrogen, superheated water, etc.
- High-quality PTFE (polytetrafluoroethylene) sealing materials and special geometric shapes are adopted to ensure reliable sealing and stable flow.
- The packing consists of 4 sets of special V-shaped reinforced PTFE and springs, which are wear-resistant and have an automatic compensation function.
- The special surface treatment of the valve stem ensures low friction between the stem and the packing as well as reliable sealing.
- It is widely used in the automatic control of the internal and external temperature processes during the vulcanization of rubber products,






Shut Off Valve

Z11 Series
Pneumatic Three-way Medium
Pressure Shut Off Valve





Order Instruction



Single Acting Normally Close, 2-way, Flange JIS20K

Dimension

Size		L	H1	H2	H	D	D1	C	T	t	n-Φd	A1	A2	A3
DN15	1/2"	146	44	164	208	95	51	70	14	1	4-15	106	100	42
DN20	3/4"	146	54	193	247	100	56	75	16	1	4-15	122	118	50
DN25	1"	167	67	233	300	125	67	90	16	1	4-19	152	147	64
DN40	1 1/2"	190	89	302	391	140	81	105	18	2	4-19	192	191	85




Single Acting Normally Close, 3-way, Flange JIS20K

Dimension

Size		L	H1	H2	H	D	D1	C	T	t	n-Φd	A1	A2	A3	R
DN15	1/2"	146	48	164	212	95	51	70	14	1	4-15	106	100	42	Rc1/2"
DN20	3/4"	146	66	193	259	100	56	75	16	1	4-15	122	118	50	Rc3/4"
DN25	1"	167	70	233	303	125	67	90	16	1	4-19	152	147	64	Rc1"
DN40	1 1/2"	190	92	302	394	140	81	105	18	2	4-19	192	191	85	Rc1 1/2"




Shut Off Valve



Single Acting Normally Close, Three-way, Three-end Flange connection

Dimension

Size		L	H1	H2	H	D	D1	C	T	t	n-Φd	A1	A2	A3
DN15	1/2"	146	85	164	249	95	51	70	14	1	4-15	106	100	42
DN20	3/4"	146	100	193	293	100	56	75	16	1	4-15	122	118	50
DN25	1"	167	115	233	348	125	67	90	16	1	4-19	152	147	64
DN40	1 1/2"	190	145	302	447	140	81	105	18	2	4-19	192	191	85



Single Acting Normally Open, Two-way, Flange connection

Dimension

Size		L	H1	H2	H	D	D1	C	T	t	n-Φd	A1	A2	A3
DN20	3/4"	146	54	223	277	100	56	75	16	1	4-15	122	118	50
DN25	1"	167	67	250	317	125	67	90	16	1	4-19	152	147	64
DN40	1 1/2"	190	89	333	422	140	81	105	18	2	4-19	192	191	85

Z12 Series
Pneumatic Two-way
Low Pressure Shut Off Valve



Technical Specification


- Operating pressure: 0-12bar (0-174bar)
- Control pressure: 3-8bar (43.5-116psi)
- Control fluid: Filtered compressed air or neutral gas
- Body material: CF8/CF8M
- Seal material: PTFE
- Actuator material: CF8
- Actuator size: 125mm(AL)
- Applicable fluid: Water, Nitrogen, Steam
- Medium temperature: -10°C — +220°C
- Ambient temperature: -10°C — +80°C
- Control type: Single acting normally closed, Double acting normally closed
- Connection type: Flange

Advantages


- Add a bearing guide at the valve cover to avoid the offset of the valve core caused by the impact of steam and to improve the service life.
- High-quality PTFE sealing materials to ensure reliable sealing.
- It can be widely used in the foam plastic industry or other harsh

Dimension

Size	Actuator (mm)	Q	A	K	L	C	H	E	n-ΦF	M	N	P	α
DN65	125	1/4"	365	485	290	3	18	145	4-18	71	120	185	45°
DN80	125	1/4"	395	545	310	3	20	180	8-18	84	135	200	22.5°



Shut Off Valve



Regulating Valve

ZMP series
Pneumatic
Regulating Valve


Technical Specification

- Operating Pressure: 0-17bar (0-246.5psi)
- Fluid Temperature: Max. 210°C
- Control Pressure: 0.2-1bar (2.9-14.5psi)
- Body material: CF8
- Applicable Fluid: High-temperature steam, Superheated water, Nitrogen, Compressed air
- Connection Type: Flange JIS 20K
(ASME CLASS300, DIN PN40, GB PN40 Customization available)

Description


This is a regulating valve with diaphragm design. It has excellent control performance and can guarantee accurate flow control. It's

Flow Curve Chart





Regulating Valve




Dimension



Normally Close, 2-way, Flange JIS 20K

SIZE		L	H1	H2	H	D	D1	C	T	t	n-Φd	A
DN15	1/2"	154	60	306	358.5	95	51	70	14	1	4-15	220
DN20	3/4"	154	60	306	358.5	100	56	75	16	1	4-15	220
DN25	1"	164	65	310	358.5	125	67	90	16	1	4-19	220

Order Instruction



Control Accessory



Technical Specification

- Stroke range: 5-35mm (Mechanical type) /5-30mm (Contactless type)
- Voltage: 12V DC-36V DC (Mechanical type) /12V DC-30V DC (Contactless type)
- Current: MAX.300mA (Mechanical type) /MAX.100mA (Contactless type)
- Indication Light: Visually feedbacks the valve's open/close status
- Temperature range: -20°C — +70°C
- Storage temperature: -30°C — +80°C
- Ambient humidity: ≤90%RH
- Protection level: IP65
- Explosion-proof: Ex ec IIC T4 Gc
- Enclosure material: PA6-GF30+PC
- Main dimension: Φ62x70
- Installation interface: G1/4, M26x1.5
- Wiring method: Unscrew the transparent cover, thread the cable through the cable opening and connect it to the required terminal.


Advantages

1. Compact size to save space.
2. Reliable performance and sensitive reaction.
3. Spring-loaded and threaded connection are easily interchangeable.
4. Quick installation and allows 360° rotation adjustment.
5. Unique slider adjustment, convenient adjustment and precise position.
6. Screw-free terminal block makes wiring more convenient.
7. Waterproof cable lock ensures internal dustproof and moisture proof.
8. A variety of input/output modes canbe realized through simple adjustments.
9. Using magnetic switch toachieve contactless feedback,prolong


Function Principle

It is used to detect and feedback both open and closed states of


Electrical Schematic



Order Instruction



Control Accessory

OP0 Series
Intelligent Positioner

Technical Specification

- Stroke range: 5–13mm, 10–28mm
- Voltage: 24V DC $\pm$ 10%
- Power consumption: < 4W
- Input signal: 0/4–20mA, 0–5/10V
- Feedback signal: Simulated signal (0/4–20mA, 0–5/10V)
Digital signal (high-level)
- Enclosure Material: PA6-GF15+PC+304
- Dimension: Φ 79x112
- Control pressure: 3–7bar (43.5–102psi)
- Temperature range: 0–60°C
- Protection level: IP65
- Explosion-proof: Ex ec IIC T4 Gc
- Mounting interface: G1/4、M26x1.5 (can be customized)

Advantages

1. Compact size to save space.
2. Reliable performance and sensitive reaction.
3. Large LCD display makes it easy to operate.
4. Standard electrical interface allows convenient wiring.
5. High adjustment precision and strong anti-interference performance.
6. Spring-loaded feedback rod for easy installation.

Electrical Terminal


Terminal	Descriptions	Color	Signal Type
1	Power+	Brown	+24VDC $\pm$ 10%
2	Input Signal+	White	0/4–20mA or 0–5/10V
3	GND	Blue	GND
4	Feedback Signal+ (Optional: Alarm output for insufficient adjustment)	Black	0/4–20mA or 0–5/10V (High electric level)
5	External sensor signal+	Grey	4–20mA

Pneumatic Terminal


Port Label	Description
P	Air input
A	Pilot port
R	Exhaust port

Function Principle

Intelligent positioner is a microprocessor-based valve regulator. The valve's open/close state is controlled by external input signals. It is widely used in industrial fluids control systems in order to enable

OP1 Series
Two-piece
Intelligent Positioner

Order Instruction



Limited suitability parts are rated as wear parts and are not included in the standard warranty conditions.

